

Package: gp^{tr} (via r-universe)

October 17, 2026

Title Language Model Agents Inside the Live 'R' Session

Version 1.0.0

Description Runs large language model agents inside the running 'R' session, so that models inspect and modify objects that are already in memory instead of re-running scripts from scratch. A single function, `peter()`, opens an interactive chat in the console or, given a prompt, runs the agent loop and returns a value that can be piped into further prompts. Supports the 'Anthropic', 'OpenAI' and 'Google Gemini' application programming interfaces, 'OpenAI'-compatible endpoints, the 'Claude Code' and 'Codex' command line tools, local 'Ollama' conversational models, and System One typed-decision models such as 'Jev', 'Clef' and 'Clef Flash' <https://typesafe.ai/blog/introducing-system-one-models-and-jev>, whose typed yes/no, choice and score answers can be used directly in `if()` and `for()` statements. Tools for reading, writing, editing and searching files and for evaluating 'R' code are implemented in 'R'; skills, extensions, Model Context Protocol ('MCP') servers, sub-agents and 'shiny' apps are supported. Sessions are recorded as 'R' scripts, 'R Markdown', 'Quarto' or 'Jupyter' documents that can be re-run. Writing files and evaluating model-generated code require the user's permission by default.

License MIT + file LICENSE

URL <https://broccolito.github.io/gptr/>,
<https://github.com/Broccolito/gptr>

BugReports <https://github.com/Broccolito/gptr/issues>

Depends R (>= 4.2.0)

Imports cli (>= 3.6.0), curl (>= 6.0.0), graphics, grDevices, jsonlite (>= 1.8.8), methods, processx (>= 3.8.0), ps (>= 1.8.0), rlang (>= 1.1.0), stats, tools, utils, yaml (>= 2.3.0)

Suggests bslib, chromote, codetools, data.table, DBI, duckdb, httpuv, keyring, knitr, later, magick, openssl, ragg, reticulate,

rmarkdown, RSQLite, rstudioapi, shiny, stringi, testthat (>= 3.2.0), vctrs, withr

Enhances repr

VignetteBuilder knitr, rmarkdown

Config/testthat/edition 3

Copyright file inst/COPYRIGHTS

Encoding UTF-8

Language en-US

NeedsCompilation no

Roxygen list(markdown = TRUE)

SystemRequirements Optional: Ollama (>= 0.35.1) for native local decision models; other optional external programs: 'claude' (Claude Code) and 'codex' (Codex) for subscription providers, 'quarto' for 'Quarto' documents, and a 'Chrome'-family browser for app screenshots.

Config/roxygen2/version 8.1.1

Config/pak/sysreqs chromium libssl-dev

Repository <https://broccolito.r-universe.dev>

Date/Publication 2026-10-17 03:06:10 UTC

RemoteUrl <https://github.com/broccolito/gptr>

RemoteRef HEAD

RemoteSha 0c4b0003ca33a58777f9ee26f1cc268c5ddde83b

Contents

as.data.frame.gptr_session_summary	4
format.gptr_risk	4
format.gptr_session	5
gptr-background	6
gptr_adapter	7
gptr_agent	8
gptr_api	9
gptr_artifacts	10
gptr_backend	11
gptr_blocks	12
gptr_cache	12
gptr_cancel	13
gptr_check	14
gptr_command	15
gptr_config	15
gptr_context_block	17
gptr_describe	18
gptr_doc	19

gpnr_egress	21
gpnr_env	22
gpnr_export	23
gpnr_fake_provider	24
gpnr_fork	26
gpnr_hook	26
gpnr_init	27
gpnr_jobs	28
gpnr_login	29
gpnr_mcp	30
gpnr_mcp_add	31
gpnr_mcp_serve	32
gpnr_models	33
gpnr_on	34
gpnr_options	35
gpnr_parallel	39
gpnr_permissions	40
gpnr_plugins	41
gpnr_policy	42
gpnr_preimage	43
gpnr_prob	44
gpnr_prompt	45
gpnr_prompt_section	46
gpnr_provider	47
gpnr_providers	48
gpnr_redact	49
gpnr_register	50
gpnr_registry	51
gpnr_reload	51
gpnr_return	52
gpnr_rewind	53
gpnr_risk	55
gpnr_router	56
gpnr_scrub	57
gpnr_security	58
gpnr_sessions	60
gpnr_skills	61
gpnr_source	62
gpnr_spec	63
gpnr_steer	64
gpnr_step	64
gpnr_tool	65
gpnr_tool_result	67
gpnr_trust	68
gpnr_usage	68
gpnr_wait	70
peter	71
print.gpnr_session	73

print.gptr_session_summary	74
str.gptr_session	75
summary.gptr_session	75

Index	76
--------------	-----------

as.data.frame.gptr_session_summary	
	<i>Convert a session summary to a data frame</i>

Description

Convert a session summary to a data frame

Usage

```
## S3 method for class 'gptr_session_summary'
as.data.frame(x, ...)
```

Arguments

- x A gptr_session_summary.
- ... Further arguments, such as row.names and optional, passed to the ordinary data frame method.

Value

An ordinary data.frame containing the complete history.

format.gptr_risk	<i>Format a risk classification</i>
------------------	-------------------------------------

Description

Format a risk classification

Usage

```
## S3 method for class 'gptr_risk'
format(x, ...)

## S3 method for class 'gptr_risk'
print(x, ...)
```

Arguments

x	A gptr_risk object.
...	Unused.

Value

format() returns a character vector: the level line, then one line per flagged call (control, bidi and zero-width characters escaped); print() returns x invisibly.

Examples

```
r = gptr_risk("x = 1; unlink('data', recursive = TRUE)")
format(r)
print(r)
```

format.gptr_session	<i>Format a session as its text</i>
---------------------	-------------------------------------

Description

Format a session as its text

Usage

```
## S3 method for class 'gptr_session'
format(x, ...)

## S3 method for class 'gptr_session'
as.character(x, ...)
```

Arguments

x	A gptr_session.
...	Unused.

Value

x\$text.

Description

`peter(..., background = TRUE)` returns the session at once while its run keeps going. A timer from the **later** package advances the run every 50 ms while the R console is idle, so you can keep working. Piping into the running session, `session |> peter("...")`, queues a steer that the agent receives after its current tool result; `gptr_wait()` waits for the session, `gptr_cancel()` aborts its run and `gptr_jobs()` lists it. Background sessions are **experimental**: they need the **later** package, and they are never used in examples or in CRAN tests. Background work is not an independent R execution thread: an inline R tool occupies the process while it runs. Returning a session does not establish idle progress in an unverified front end; inspect its status and use a blocking wait when needed.

How a background run behaves

- Streams progress at every idle tick. While a blocking gp_{tr} call runs (`peter()`, `gptr_wait()`, `gptr_step()` or a console turn), that call advances the background runs as well and the background timer does nothing.
- R tools of a background run execute at an idle tick when `options(gptr.background_tools = "idle")` (the default). The console is busy while such a tool runs; Ctrl-C then opens the pause menu. With "wait" they run only inside a blocking gp_{tr} call such as `gptr_wait()`.
- A background run never asks a question at the idle console. When it needs an approval or an answer at an idle tick, the action is not performed: the agent is told that the user will be asked, its run stops, and the session moves to status "waiting" with a notice. At your next `gptr_wait()`, `peter()` call or console turn the session continues with one more model request, the agent repeats the call, and you are asked as usual. A message piped into a waiting session is delivered when it continues.
- `gptr_cancel()` stops a running background session. A waiting session has no run to cancel: `gptr_jobs(kill = TRUE)` stops it (together with every other job).
- When an R tool changed objects in your workspace at an idle tick, one notice names them.
- Under Rscript, knitr and Quarto there is no idle console: background runs progress only inside blocking gp_{tr} calls.

Support matrix

Front end

Terminal R on macOS
 Terminal R on Linux
 Rscript, knitr, Quarto
 RStudio
 Positron, Jupyter (IRkernel), Rgui
 Windows consoles

Status

verified: idle ticks, pause menu, pipe steering
 unverified (the same **later** event loop as macOS)
 no idle ticks by design; progress inside blocking gp_{tr} calls
 unverified (**later** is expected to run callbacks at its idle console)
 unverified
 unverified; a timer polls the reactor, so child pipes are served

Options

gptr.background_tools "idle" (default) or "wait": whether R tools of background runs execute at idle ticks or wait for the next blocking gptr call.

See Also

[peter](#), [gptr_wait](#), [gptr_cancel](#), [gptr_steel](#), [gptr_jobs](#)

gptr_adapter	<i>Define a wire adapter</i>
--------------	------------------------------

Description

An adapter turns gptr's request context into one provider's wire format and its stream back into gptr events. HTTP and process adapters give build() and parse(); inprocess adapters give stream(), a generator factory; classifier adapters give classify.

Usage

```
gptr_adapter(
  api,
  transport = c("http_sse", "http_ndjson", "http_json", "process_jsonl", "inprocess"),
  build = NULL,
  parse = NULL,
  stream = NULL,
  classify = NULL,
  capabilities = list()
)
```

Arguments

api	The wire api this adapter implements (the name providers bind to).
transport	"http_sse", "http_ndjson", "http_json", "process_jsonl" or "inprocess".
build	function(model, context, opts) returning a request spec.
parse	function(model, opts) returning a stream normalizer.
stream	function(model, context, opts) returning a generator (inprocess).
classify	Named list for classifier adapters: build(model, state, questions, opts) and parse(model, status, headers, body, questions), or run(model, state, questions, opts) for inprocess. Classifier response parsing has a separate signature from the ordinary chat stream parse(model, opts).
capabilities	Named list of adapter capabilities.

Value

A spec of class c("gptr_adapter", "gptr_spec").

Examples

```
gptr_adapter("echo", transport = "inprocess",
  stream = function(model, context, opts) {
    state = new.env()
    state$done = FALSE
    function() {
      if (state$done) return(NULL)
      state$done = TRUE
      list(events = list())
    }
  })
```

gptr_agent

Define a sub-agent

Description

An agent definition names a specialist for `peter(agents = ...)`: its model, tools, skills, system text, backend, preset and limits. model and skills may be bare identifiers; they are stored unevaluated (as written) and resolved by the gateway. `gptr_agent("name")` alone (or with only file) loads a saved definition. Package code should pass strings.

Usage

```
gptr_agent(
  name = NULL,
  description = NULL,
  model = NULL,
  tools = NULL,
  skills = NULL,
  system = NULL,
  backend = c("auto", "inline", "worker", "cli"),
  preset = "minimal",
  max_turns = NULL,
  mode = NULL,
  objects = NULL,
  export = NULL,
  returns = NULL,
  file = NULL
)
```

Arguments

name	Agent name.
description	One line describing the specialist.
model	Model reference: a string, a bare identifier or a provider spec.
tools	Tool names (or specs) the agent may use.

skills	Skills to preload.
system	System text of the agent.
backend	"auto", "inline", "worker", "cli" or a registered backend name.
preset	Tool preset of the agent's session.
max_turns	Turn limit, or NULL.
mode	Permission mode ("plan", "manual", "edits", "auto"), or NULL to inherit.
objects	Names of objects the agent may see.
export	Names of objects the agent returns.
returns	JSON Schema of a structured answer, or NULL.
file	Path of an agent definition file.

Value

A spec of class c("gp_{tr}_agent", "gp_{tr}_spec").

Examples

```
gptr_agent("stats", description = "Statistical reviewer", model = "anthropic/claude-opus-5-5",
  skills = "statistics")
```

gp _{tr} _api	<i>Extension API version and features</i>
-----------------------	---

Description

The version of gp_{tr}'s public extension API (independent of the package version) and the features this build offers: kind.<name> for every registered kind, event.<name> for every cataloged event, and the named features lazy_activation, declarations, ctx.decide, ctx.secret, route and services. Plugins test features instead of comparing versions.

Usage

```
gptr_api()
```

Value

A gp_{tr}_api list with version (a package_version) and features (character).

Examples

```
gptr_api()$version
"kind.router" %in% gptr_api()$features
```

gptr_artifacts	<i>List, open, relaunch and stop artifacts</i>
----------------	--

Description

Artifacts are Shiny apps the agent builds from objects in your session. It writes `.gptr/artifacts/<id>/app.R` and launches it with `peter$app("<id>", data = c("obj"))`, which snapshots the named objects into an immutable version directory (`v001/`, `v002/`, ...) and serves it from a supervised background R process on `127.0.0.1`, so the console stays free. `gptr_artifacts()` lists the artifacts of the workspace (`.gptr/`, else a temporary directory) and manages their processes.

Usage

```
gptr_artifacts(id = NULL, open = FALSE, stop = FALSE, version = NULL)
```

Arguments

<code>id</code>	NULL to list every artifact, or the id of one artifact.
<code>open</code>	TRUE to open the artifact in the IDE viewer or the browser (only in an interactive session); a stopped artifact is relaunched first.
<code>stop</code>	TRUE to stop the artifact's process (interrupt, a 3 s grace, then the process tree is killed).
<code>version</code>	The number of a stored version (2 for <code>v002/</code>) to relaunch and make current.

Details

The built-in `kind = "html"` uses a working `page.html` and a Shiny serving wrapper. Both built-in kinds need Shiny to launch. `peter$app(..., launch = FALSE)` creates a version without launching it; startup and browser checks therefore remain unperformed. Browser session checks and screenshots additionally need `chromote` and `Chrome`. A check value of `NA` means it was skipped. Separate processes organize execution but are not OS sandboxes.

Value

Without `id`, a `gptr_artifacts` data frame with the columns `id`, `title`, `version` (the current version), `status` (running, stopped or failed), `url`, `pid`, `bytes` (disk use of the artifact directory) and `path` (the working copy). With `id`, the `gptr_artifact` handle: a list with `id`, `title`, `kind`, `version`, `url` (it carries the launch's access token), `path`, `status`, `checks` (parse, launch, http and session, each TRUE, FALSE or NA, plus messages), `screenshot` and `session`; it is returned invisibly after `open`, `stop` or `version`.

Security considerations

An artifact runs model-written code in a separate R process whose environment holds none of your registered secrets. It listens only on `127.0.0.1`, and every launch gets a new 128-bit access token that its URL carries (`?gptr_token=`); without the `openssl` package on Windows there is no token and a notice says so. The data snapshot in `vNNN/data/` is a copy of the objects named in `data`; the `.gptr/.gitignore` that `gptr_init()` writes keeps it and `run/` out of git.

Options

gp_{tr}.artifact_max_bytes (default 5e8): the largest total object.size() of the objects one version may snapshot; above it peter\$app() signals gp_{tr}_error_artifact_too_large.

See Also

vignette("tools-and-artifacts", package = "gp_{tr}") for working files, data snapshots, checks and lifecycle examples.

Examples

```
gptr_artifacts()           # an empty listing when no artifact exists
```

gp _{tr} _backend	<i>Define a sub-agent backend</i>
---------------------------	-----------------------------------

Description

A backend runs child sessions: start(spec, ctx) returns a handle the reactor can poll, cancel(handle) stops it and every process it started. Backends never block the reactor for more than 50 ms.

Usage

```
gptr_backend(name, start, poll = NULL, cancel, capabilities = list())
```

Arguments

name	Backend name, usable as backend = <name>.
start	function(spec, ctx).
poll	function(handle) or NULL.
cancel	function(handle).
capabilities	Named list: parallel, live_objects, ask.

Value

A spec of class c("gp_{tr}_backend", "gp_{tr}_spec").

Examples

```
gptr_backend("echo", start = function(spec, ctx) NULL, cancel = function(handle) NULL)
```

gptr_blocks

List the agent blocks of a document

Description

Reads an .R, .Rmd, .qmd or .ipynb document and lists its gptr blocks with their status: fresh (the owning call's prompt matches), stale (the prompt changed, or no call owns the block), user-edited (the body no longer matches its sha) or undone (made inert by a rewind). Interpolated values are only known when the call runs, so they are not checked here. It reads the document; the only write is that blocks an Rscript run queued before it was killed are applied first (never over your edits).

Usage

```
gptr_blocks(file)
```

Arguments

file Path of the document.

Value

A gptr_blocks data frame with columns id, lines, prompt, status, model, date, tokens, cost, session.

Examples

```
f = tempfile(fileext = ".R")
writeLines(c('peter("add one")',
             "# >>> gptr:7f3a21 model=fake/fake-1 date=2026-09-29 prompt=3b1c9a0e77d2",
             "x = 1 + 1", "# <<< gptr:7f3a21"), f)
gptr_blocks(f)
```

gptr_cache

Inspect, prune or clear gptr's caches

Description

info lists the System 1 answer cache, the System 2 answer cache used for replay, temporary spill files and unapplied document sidecars (deferred or pending blocks; they are never removed here: apply them with gptr_doc(path, sync = TRUE)). prune removes System 2 answers whose block is neither in its document nor queued for it in a sidecar, System 1 answers unused for 90 days, temporary files older than getOption("gptr.spill_days", 7) days and older refreshed model catalogs; clear removes a kind entirely.

Usage

```
gptr_cache(
  action = c("info", "prune", "clear"),
  kind = c("all", "s1", "s2", "tmp")
)
```

Arguments

action "info", "prune" or "clear".
kind "all", "s1", "s2" or "tmp".

Details

Clearing the System 2 answer cache does not remove the R code of document blocks, but saved answers needed to reconstruct a replayed call may no longer be available.

Value

info: a gp_{tr}_cache_info data frame with columns kind, entries, bytes, oldest, path. prune and clear: the number of files removed, invisibly.

Examples

```
gptr_cache()
gptr_cache("prune", "tmp")
```

gp _{tr} _cancel	<i>Cancel running sessions</i>
--------------------------	--------------------------------

Description

Aborts the run of a session (or of each session in a list): transfers are canceled, child processes stopped, the partial turn recorded as aborted, queued items moved to dropped, and the status set to aborted. Idle sessions are left alone.

Usage

```
gptr_cancel(x)
```

Arguments

x A session or a list of sessions.

Value

x, invisibly.

Examples

```
session = peter("long task", model = gptr_fake_provider(list(list(hang = TRUE))),
  .run = FALSE)
gptr_cancel(session)
```

gp_{tr}_check*Check an extension for conformance***Description**

Runs gp_{tr}'s conformance suite, offline, in a scratch registry. For a spec: its fields and kind validator, schema validity, direct tool descriptions of at most 400 tokens, prompt-section budgets, empty-input handling of tools, the permission matrix for policies, start and cancel for backends, and wire-fixture replay for adapters when the adapter checker is available. For a factory function(gp_{tr}): it loads, registers something, takes no action at load, and each registered spec passes. For an installed package name: its inst/gp_{tr}/plugin.json manifest, API requirement, factory, every provided capability, and bare gp_{tr} identifiers in its code.

Usage

```
gptr_check(x, error = FALSE, tokens = FALSE)
```

Arguments

x	A spec, a factory function(gp _{tr}), or the name of an installed plugin package.
error	TRUE to signal gp _{tr} _error_conformance when a check fails.
tokens	TRUE to also report declaration costs and the printed cost of each member's examples.

Value

A gp_{tr}_check data frame with columns target, check, ok and message.

Examples

```
gptr_check(gptr_tool("add", "Add two numbers",
  parameters = list(type = "object", required = I(c("a", "b")),
    properties = list(a = list(type = "number"),
      b = list(type = "number"))),
  fun = function(a, b) a + b, exposure = "r", namespace = "demo"))
```

gp _{tr} _command	<i>Define a slash command</i>
---------------------------	-------------------------------

Description

A console command /name args: handler(args, ctx) gets the raw text after the name and returns NULL, a character vector (printed) or list(prompt = "...") (sent as a prompt).

Usage

```
gptr_command(name, handler, description = NULL, complete = NULL)
```

Arguments

name	Command name without the leading /.
handler	function(args, ctx).
description	One line for /help.
complete	Optional function(prefix, ctx) returning completion candidates. Stored as metadata for frontend integrations; the built-in console does not currently invoke it.

Value

A spec of class c("gp_{tr}_command", "gp_{tr}_spec").

Examples

```
gptr_command("rows", function(args, ctx) paste("rows:", nrow(mtcars)), description = "Show rows")
```

gp _{tr} _config	<i>Show or change gp_{tr}'s settings</i>
--------------------------	--

Description

With no arguments, returns the effective settings with the layer each value came from: package defaults < user settings.json < project .gp_{tr}/settings.json (an untrusted project only tightens mode, context, record, permission rules and local-only inference) < the user-level project file < options(gp_{tr}.*). With named arguments, sets those keys in one scope.

Usage

```
gptr_config(..., .scope = NULL)
```

Arguments

<code>...</code>	Named settings, e.g. <code>mode = manual</code> , <code>model = sonnet</code> , <code>budget = list(cost = 2)</code> .
<code>.scope</code>	NULL (the project when a <code>.gptr/</code> workspace exists, else this session), or "session", "project" or "user".

Details

`model`, `small_model`, `system1`, `mode` and `preset` take bare names (`mode = plan`); NULL removes a key from the scope. `egress` (the providers you allow automatic context to go to) is accepted only at user scope. Local-only Ollama inference (`providers = list(ollama = list(local_only = FALSE))`) can be turned off only at user or session scope; a project can only keep it on. Called from model code during a run, it is refused.

The "session" scope means this R process, not one conversation. User settings live at `tools::R_user_dir("gptr", "config")/settings.json`; project settings live in `.gptr/`. A no-argument call always reads effective values, even when `.scope` is supplied. Inspect `attr(gptr_config(), "sources")` to see their origins. Named lists merge with lower layers; protected objects such as providers must be set as a whole named list.

Value

Without arguments, a `gptr_config` list. Otherwise the previous values in that scope, invisibly (a named list; NULL where the key was unset).

Choosing controls

Use settings for defaults such as `model`, `mode`, `context`, `budget`, `record`, `replay` and registered extension selections. Use [gptr_options](#) for transport timeouts, output caps, undo retention and concurrency. Arguments to [peter\(\)](#) choose values for one call, within inherited safety restrictions. `vignette("configuration", package = "gptr")` groups all core settings and options and explains trust and scope.

See Also

[gptr_init\(\)](#), [gptr_trust\(\)](#), [gptr_permissions\(\)](#) and [gptr_options](#).

Examples

```
old = gptr_config(mode = plan, .scope = "session")
gptr_config()$mode
gptr_config(mode = old$mode, .scope = "session")
```

gptr_context_block	<i>Define a context block</i>
--------------------	-------------------------------

Description

A block of context the model receives in user messages: `provide(ctx, budget)` returns text (or NULL to skip). `placement` puts it in the first message, in later turns, or both; turn blocks equal to their previous text are skipped. `authority = "operator"` is accepted only from user, plugin and built-in records.

Usage

```
gptr_context_block(  
    name,  
    provide,  
    placement = c("turn", "first", "both"),  
    authority = c("data", "operator"),  
    budget = 300L,  
    order = 650L  
)
```

Arguments

<code>name</code>	Block name (the tag it is wrapped in).
<code>provide</code>	<code>function(ctx, budget)</code> .
<code>placement</code>	"turn", "first" or "both".
<code>authority</code>	"data" or "operator".
<code>budget</code>	Token budget; longer text is truncated.
<code>order</code>	Position among blocks.

Value

A spec of class `c("gptr_context_block", "gptr_spec")`.

Examples

```
gptr_context_block("lab_notebook", function(ctx, budget) "Experiment 12: cohort B only.",  
    placement = "first", order = 650L)
```

gptr_describe

Compact, budgeted description of an R object

Description

An S3 generic used for the <attached> and <workspace> context blocks, `peter$describe()` and console mentions. Methods return successively richer levels of detail and the richest level whose estimated size fits budget is returned. Methods never force promises, never do I/O (no `dbListTables()`, no `collect()`) and never call `str()` on the object. Packages add methods with a delayed S3method(`gptr::gptr_describe`, <class>).

Usage

```
gptr_describe(x, budget = 150L, ...)

## Default S3 method:
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'data.frame'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'matrix'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'list'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'environment'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class '`function`'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'formula'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'lm'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'dgCMatrx'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'Seurat'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'SingleCellExperiment'
gptr_describe(x, budget = 150L, ..., level = NULL)
```

```
## S3 method for class 'ArrowTabular'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'Dataset'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'DBIConnection'
gptr_describe(x, budget = 150L, ..., level = NULL)

## S3 method for class 'ggplot'
gptr_describe(x, budget = 150L, ..., level = NULL)
```

Arguments

<code>x</code>	Any R object.
<code>budget</code>	Estimated tokens, at least 20 (default 150).
<code>...</code>	Passed to methods; built-in methods accept <code>level</code> (1 = header only; larger values give more detail).
<code>level</code>	Built-in methods: the detail level to return (default: the richest that fits).

Value

A character vector of lines; the first is a header `<class> shape, size`.

Examples

```
gptr_describe(mtcars, budget = 60)
gptr_describe(as.Date("2026-01-01") + 0:9)
```

gptr_doc

Bind this R process to a history document

Description

`gptr_doc(path)` binds every `peter()` call of this R process, at the console and in scripts, to a history document, and is your explicit consent that `gptr` writes agent blocks into it. Nothing is written until a block is recorded. `gptr_doc(FALSE)` removes the binding and `gptr_doc()` shows it. `sync = TRUE` writes the blocks that were recorded while the document could not be written: a Jupyter notebook that was open, or the deferred writes of an Rscript run that was killed.

Usage

```
gptr_doc(path = NULL, format = NULL, sync = FALSE)
```

Arguments

path	NULL to return the current binding, FALSE to remove it, or the path of an .R, .Rmd, .qmd or .ipynb document.
format	NULL (from the file extension) or the format of that extension: "r", "rmd", "qmd" or "ipynb"; "transcript" records console turns into an .R file as one steered session.
sync	TRUE applies the pending blocks of the document now.

Details

Eligible top-level calls and pipe chains own document blocks; calls nested inside loops or functions do not. Binding supplies recording consent even when automatic recording is off, but `.opts = list(record = FALSE)` suppresses recording for that call. Binding does not reconstruct earlier unrecorded turns. A narrative summary or model-generated script draft needs review and execution checks before it can serve as a reproducible workflow.

Value

With `path = NULL`, the binding `list(path, format)` or NULL, visibly. Otherwise the previous binding, invisibly.

Options

Options of history documents (?gptr_options collects every option): `gptr.record` (settings, "ask"): "auto" records into documents without asking, "off" prevents automatic recording; an explicit binding supplies consent. Also the settings key `record`, which a project can only tighten. A call's `.opts = list(record = FALSE)` opts out even when bound; `.opts = list(record = TRUE)` retains the usual consent checks. `gptr.replay` (settings, "auto"): the replay mode "auto", "replay", "live" or "record" (also the `GPTR_REPLAY` environment variable); a call's `replay = argument` wins. `gptr.doc_output_lines` (12): #> output lines recorded per execution. `gptr.doc_source_frames` (TRUE): FALSE stops gptr from reading `source()` frames to find calls in scripts sourced without `srcrefs`. `gptr.spill_days` (7): `gptr_cache("prune")` removes temporary files older than this.

Examples

```
f = tempfile(fileext = ".R")
writeLines("library(gptr)", f)
gptr_doc(f)
gptr_doc()
gptr_doc(FALSE)
```

Description

gptr sends data to a model provider only when you run a prompt with that provider's model. The package itself collects nothing: there is no telemetry, no usage reporting and no network access when the package loads. This page lists what a request contains so that you can decide what may leave your machine.

Details

R tools compute on objects already in memory; a large dataset does not need to be uploaded in full for a conversational agent to analyze it. Descriptions and tool results can still contain data values. Native typed decision inputs use the separate encoding described below.

What a request contains

- Your prompt and the conversation so far.
- With summary context, a budgeted description of each attached object (its class, dimensions, column names and types and a few values); a small object can appear in full.
- Automatic context: a short listing of the objects in the evaluation environment (names, classes and sizes), the R version, platform and available packages, and the project instruction files (AGENTS.md, CLAUDE.md, .gptr/vignette.Rmd).
- Tool results: the printed output of R code the model ran, the parts of files it read, and images of plots it made. In manual mode every action that is not known to be read-only needs your approval before its result can be sent.

A System 1 question (a classifier model such as Jev) sends the inputs themselves: each element of a vector (text up to 100,000 characters), each row of a data frame as a record, a description of larger objects, and for a piped session its last answer (at most `gptr.sl_state_max` characters). Do not ask System 1 questions about data that may not leave your machine.

Registered secrets are replaced by markers before anything is sent.

Limiting automatic context

`.opts = list(context = "names")` sends workspace object names and attached-object headers, and `.opts = list(context = "none")` suppresses workspace and attached-object descriptions. Prompts, tool results and native typed decision inputs have their own paths. Attach only the objects the task needs. The plan mode permits actions classified as read-only so you can inspect a proposed workflow before allowing changes to your workspace.

Acknowledgment

The first time you use a provider (or a command-line route such as `claude_code` or `codex`) in an interactive session, gptr shows what automatic context is sent and records your acknowledgment in your user settings. A non-interactive run with a provider that was never acknowledged stops with

a `gptr_error_egress` condition. Record the acknowledgment once with `gptr_config(egress = list(anthropic = "ack"), .scope = "user")` (this replaces the stored list, so name every provider you use), or run with `.opts = list(context = "none")`. Offline providers such as `gptr_fake_provider()` and local providers on a loopback address need no acknowledgment. An Ollama server can forward requests to cloud models, so Ollama is exempt only while its local-only inference is on (the default; see providers in `gptr_config()`).

Other network use

`gptr` contacts nothing else on its own. The model catalog is refreshed only by `gptr_models(refresh = TRUE)`, reachability checks run only with `gptr_providers(check = TRUE)`, and MCP servers, sub-agents and command-line tools are contacted only when a session uses them. The claude and codex command-line routes send the conversation through those vendors' tools under their own terms.

See Also

`gptr_security`, `gptr_options`, `gptr_providers()`, `gptr_config()`.

`gptr_env`

Load keys from a .env file

Description

Reads a `.env` file with `gptr`'s own parser (a UTF-8 byte-order mark, CRLF line ends, export prefixes, single and double quotes, multi-line quoted values, `#` comments and hyphenated names such as `jev-key` are understood), maps aliases onto canonical variable names (`jev-key`, `JEV_KEY`, `JEV_API_KEY` and `TYPESAFE_KEY` become `TYPESAFE_API_KEY`; a line spelled exactly as the canonical name wins over an alias), registers secret values in `gptr`'s vault for redaction, and exports the canonical names with `Sys.setenv()`. Plain configuration fields with suffixes such as `_URL` or `_PATH` are not registered as secrets. It never prints, logs or returns a value.

Usage

```
gptr_env(
  path = ".env",
  aliases = NULL,
  set_env = getOption("gptr.env_export", TRUE),
  override = FALSE,
  quiet = FALSE
)
```

Arguments

<code>path</code>	Path of an existing <code>.env</code> file.
<code>aliases</code>	<code>NULL</code> , or a named list of extra aliases, <code>canonical = c("alias", ...)</code> , added to the built-in table and to the registered <code>env_alias</code> specs.

set_env	If TRUE, export the canonical names to the environment of this R process; if FALSE, keep the values in the vault only. Defaults to <code>getOption("gptr.env_export", TRUE)</code> .
override	If TRUE, overwrite variables that are already set.
quiet	If TRUE, do not report what was loaded.

Value

Invisibly, a `gptr_env_report` data frame with columns `name` (as spelled in the file), `variable` (the canonical name), `secret`, `fingerprint` and `action` ("set", "registered", "skipped" or "duplicate"), and the attribute `bad_lines` (the numbers of malformed lines). It holds names and fingerprints, never values.

Examples

```
f = tempfile(fileext = ".env")
writeLines("jev-key=example-not-a-real-key-123", f)
gptr_env(f, set_env = FALSE)$variable
unlink(f)
```

gptr_export	<i>Export a recorded R document as ordinary R or a clean Peter script</i>
-------------	---

Description

Reads a synchronized `.R` history without executing it, asking a model or recovering pending writes. In "r" format the original Peter statements become comments and their recorded R stays executable. In "peter" format calls stay active and recorded R becomes comments, so it is not executed a second time. User R and comments keep their source order.

Usage

```
gptr_export(file, to, format = c("r", "peter"))
```

Arguments

file	An existing <code>.R</code> document with fresh recorded blocks.
to	A new <code>.R</code> path in an existing directory. Existing paths are never replaced.
format	"r" (default) or "peter".

Details

Only bare or symbol-assigned literal Peter calls and Peter-only native pipelines are admitted. Distinct statements sharing a line (including semicolon-separated statements), mixed pipelines, nested or computed calls, pending writes, missing or edited blocks, secret markers and interpolated-input hashes are refused. Raw exports also refuse ordinary code that uses a removed session handle. The Peter format retains such ordinary references, since its calls remain active. Feedback follows each pipeline operand when calls end on separate lines and only its pipe operator or a comment follows the closing call. Feedback follows the next operand's indentation (at most 74 characters); other layouts keep feedback after the complete statement. Peter calls already show their prompts, so only raw R adds prompt comments. Long raw prompt comments wrap at eighty characters. Strip the recorded-prompt prefix from the first line and the two-character comment prefix from continuations, then join without separators to recover the complete escaped R string literal. A Peter-only pipeline on one line keeps grouped feedback after the statement. Call source is never reformatted.

A completed-turn identity and matching source hashes establish a recorded snapshot, not verified execution or a complete session. Ordinary console input and `record = FALSE` effects cannot be reconstructed. External files, objects and package versions must still be supplied. Remaining user code may use `gptr` or perform network and filesystem operations. Captured `#>` output is limited to twelve lines per block and eighty characters per line; outputs are comments. Encoding, line endings and the final newline follow the input file. A UTF-8 byte order mark is preserved; source that exported file with `source(to, encoding = "UTF-8-BOM")`.

Value

Invisibly, the normalized destination path.

See Also

[gptr_doc\(\)](#), [gptr_source\(\)](#), [gptr_blocks\(\)](#)

Examples

```
input = tempfile(fileext = ".R")
output = tempfile(fileext = ".R")
writeLines(c("x = 1", "# Keep ordinary code and comments.", "y = x + 1"), input)
gptr_export(input, output)
readLines(output)
unlink(c(input, output))
```

<code>gptr_fake_provider</code>	<i>A scripted, offline fake model provider</i>
---------------------------------	--

Description

`gptr_fake_provider()` returns a provider spec that plays a script instead of calling a model. It needs no network and no keys, so examples, tests and documents can run `gptr` end to end offline. Use it as `model = <spec>` or register it with `gptr_register()`.

Usage

```
gptr_fake_provider(script, name = "fake", type = c("chat", "classifier"))
```

Arguments

<code>script</code>	A list of replies or a function (see Details).
<code>name</code>	Provider id: lower-case letters, digits and -.
<code>type</code>	"chat" (the default) or "classifier".

Details

A chat script is a list of replies (request i gets reply $\min(i, \text{length}(\text{script}))$), so the last reply repeats) or a function of the request returning one reply. The request is a list with `n`, `model`, `system`, `tools`, `messages`, `last_user`, `last_results` and `params`. A reply is a string (the answer text) or a list with any of: `text`; `thinking` and `signature`; `tool` with `input` and `id` (one tool call); `tools` (a list of `list(name, input)` for parallel calls); `stop` ("length", "refusal", "pause" or "stop"); `error` with `status` and `after` (fail after after text deltas); `overflow` = TRUE; `hang` = TRUE; `json` (a structured answer); and the modifiers `delay`, `gap`, `chunk` and `usage`.

A classifier script (type = "classifier") answers System 1 questions: a list of answers (recycled the same way, one answer per question asked) or `function(state, question)`. An answer is a probability for yes/no questions, a named probability vector for choices, a vector of level probabilities for scores, or `list(error =, status =)`. Classifier results use the provider-neutral decision shape and report calibration as unknown (NA).

Value

A provider spec: a list of class `c("gptr_provider", "gptr_spec")` with `id` = `name`, `api` "fake" or "fake-classifier", one `model` ("`<name>/<name>-1`", or "`<name>/<name>-s1`" for classifiers), `offline` = TRUE, the `script`, and `log`, an environment whose `requests` element lists every request the provider received.

Examples

```
fake = gptr_fake_provider(list(
  list(tool = "r", input = list(code = "n = nrow(d)")),
  "There are 32 rows."
))
fake$models[[1]]$ref
fake$offline

judge = gptr_fake_provider(list(0.93), name = "judge", type = "classifier")
judge$models[[1]]$ref
```

gptr_fork

Fork a session

Description

Creates a new idle session whose transcript is the source path up to a cut, with the same entry ids. Nothing live is shared (listeners, queue, run, lock, usage); the fork's file is written lazily at its first own message, with parentSession and gptr.forkOf in its header. The fork's workspace is an overlay of the source's kept home: it reads every object of the source at zero cost, and its writes stay in the overlay.

Usage

```
gptr_fork(s, at = NULL, envir = c("overlay", "shared"))
```

Arguments

s	A gptr_session: the source.
at	NULL (the last closed boundary; a running source is cut there), an integer $k \geq 0$ (the end of turn k ; 0 is an empty conversation) or an entry id.
envir	"overlay": the fork evaluates in new.env(parent = <source home>); "shared": the same home.

Value

A new idle gptr_session.

Examples

```
fake = gptr_fake_provider(list("A", "B"))
session = peter("first", model = fake)
branch = gptr_fork(session)
branch |> peter("branch")
c(session$turns, branch$turns)
```

gptr_hook

Define an event hook

Description

A hook runs handler(event, ctx) for one event of the catalog (see gptr_api())\$features) or for a plugin channel named "<plugin>:<topic>". What the handler may return depends on the event: patches for tool_result, a decision for tool_call, nothing for notifications. Handlers of tool_call, permission_request and document_write fail closed: an error blocks or denies, and a tool_call answer with an unknown decision (anything but "block", "modify" with an input list, or "allow"; for example "deny") blocks.

Usage

```
gptr_hook(event, handler, matcher = NULL)
```

Arguments

event	Event name.
handler	function(event, ctx).
matcher	NULL, a tool-name glob such as "mcp_*", or function(event) returning TRUE for events the handler wants.

Value

A spec of class `c("gptr_hook", "gptr_spec")`, named after its event.

Examples

```
gptr_hook("tool_result", function(event, ctx) NULL, matcher = "r")
```

gptr_init	<i>Create the project workspace .gptr/</i>
-----------	--

Description

Creates `.gptr/` with `settings.json`, `skills/`, `agents/`, `prompts/`, and (by default) the project-instructions file `vignette.Rmd` and `.gitignore`. Existing files are never overwritten, so calling it again is safe. There is no default path: without path `gptr` asks `Create .gptr/ in <project>? [y/N]` when you can answer, and signals an error otherwise. Creating the workspace is consent to write there; it is not trust: `gptr` then asks separately whether to trust the project (see [gptr_trust\(\)](#)). In a package source it offers the `^\.gptr$` line for `.Rbuildignore` and never writes it silently.

Usage

```
gptr_init(path, instructions = TRUE, gitignore = TRUE)
```

Arguments

path	The project directory (it must exist).
instructions	Write <code>vignette.Rmd</code> from the template when it is absent.
gitignore	Write <code>.gptr/.gitignore</code> from the template when it is absent.

Value

The absolute path of `.gptr/`, invisibly (NULL when you declined).

Examples

```
d = tempfile("proj")
dir.create(d)
gptr_init(d)
list.files(file.path(d, ".gptr"), all.files = TRUE)
unlink(d, recursive = TRUE)
```

gptr_jobs

List or stop gptr's background jobs and child processes

Description

Lists the job table of this R process: background sessions, `peter$bg()` jobs, Shiny artifacts, the MCP server started by `gptr_mcp_serve()`, sub-agent workers and subscription-CLI children. A finished job whose stop was requested reads stopped or aborted, never error. Unavailable status information is shown as unknown.

Usage

```
gptr_jobs(kill = FALSE)
```

Arguments

kill TRUE stops every job (sessions are canceled, processes are killed together with their process tree) and returns the table of what was stopped, invisibly.

Value

A `gptr_jobs` data frame with the columns `id`, `kind` (session, bg, artifact, mcp_serve, worker, cli), `name`, `pid`, `status` and `started`.

Options

Options of the transport and process layer (?gptr_options collects every option):

- `gptr.max_active` (8): concurrent HTTP transfers (global).
- `gptr.connect_timeout` (20), `gptr.first_byte_timeout` (120), `gptr.idle_timeout` (90): seconds; there is no total timeout on streams.
- `gptr.max_retry_delay` (60): seconds; a longer retry-after fails fast.
- `gptr.max_attempts` (4): transport attempts per request.
- `gptr.wire_log` (FALSE): TRUE writes one redacted JSON line per request start and end to `<workspace root>/cache/tmp/wire-<session id>.jsonl`; a path must lie inside the workspace root or `tempdir()`.
- `gptr.supervise` (NULL): processx supervision of children; NULL means on, except under R CMD check.
- `gptr.stdin_timeout` (60): seconds a child may take to accept pending stdin bytes.

Examples

```
gptr_jobs()
```

gptr_login

Sign in to a model provider or an MCP server

Description

Stores a credential for a model provider (for example "openrouter") or for an MCP server ("mcp:<server>"). With method = "auto", providers and MCP servers that support OAuth get the authorization-code flow with PKCE (S256): a page on 127.0.0.1 receives the redirect when 'httpuv' and 'later' are installed; otherwise you paste the address your browser ends on. Everything else gets masked key entry. Credentials go to the credential store (auth.json, readable only by you, or a keyring reference); access tokens stay in memory. A tool call never opens a browser: when an MCP server needs a sign-in, the call fails with an error naming this function.

Usage

```
gptr_login(provider, method = c("auto", "oauth", "key"))
```

```
gptr_logout(provider)
```

Arguments

provider A provider id such as "openrouter", or "mcp:<server>" for an MCP server.

method "auto" (default), "oauth" (the browser flow only) or "key" (key entry).

Value

gptr_login() returns TRUE invisibly; gptr_logout() removes the stored credential and forgets the access token held in memory, and returns TRUE invisibly when it removed something, else FALSE.

Examples

```
if (interactive()) {
  gptr_login("openrouter")
  gptr_logout("openrouter")
}
```

gptr_mcp

*List MCP servers and their tools***Description**

Without tools, lists gptr's servers (the user `mcp.json` and, in a trusted project, `.gptr/mcp.json`) together with the servers configured for Claude Code, Claude Desktop, Codex, Cursor, VS Code and Pi, which gptr reads but never edits. Nothing is started: the era and the tool counts come from gptr's caches. With `tools = TRUE`, lists the tools of server (or of every usable server) with their R signatures and catalog cost, from the cache when it is fresh and otherwise by connecting (which starts stdio servers). Servers of an untrusted project are listed but never started.

Usage

```
gptr_mcp(server = NULL, tools = FALSE, refresh = FALSE)
```

Arguments

server	A server name, or NULL for all.
tools	TRUE to list tools instead of servers.
refresh	TRUE to reconnect and refresh the caches.

Value

A `gptr_mcp_servers` data frame (name, source, transport, era, status, tools, exposure, tokens, trusted) or, with `tools = TRUE`, a data frame with server, tool, signature, exposure and tokens.

See Also

[gptr_mcp_add](#), [gptr_mcp_remove](#), [gptr_login](#), [gptr_mcp_serve](#); `vignette("mcp", package = "gptr")` for setup, authentication and tool calls.

Examples

```
gptr_mcp()
```

gptr_mcp_add

*Add or remove an MCP server in gptr's configuration***Description**

`gptr_mcp_add()` writes a server into gptr's own `mcp.json`: the user file under `tools::R_user_dir("gptr", "config")`, or `.gptr/mcp.json` of the project (used only when you trust the project). It never edits another harness's files. Give exactly one of `command` (a server started as a local process speaking `stdio`) and `url` (a Streamable HTTP server). Secret values in `env` and `headers` must be `${VAR}` placeholders: they are expanded from the environment when gptr connects and never stored. Nothing connects until a tool is used.

Usage

```
gptr_mcp_add(
  name,
  command = NULL,
  args = character(),
  url = NULL,
  env = NULL,
  headers = NULL,
  exposure = "r",
  timeout = 60,
  scope = c("user", "project")
)

gptr_mcp_remove(name, scope = c("user", "project"))
```

Arguments

<code>name</code>	Server name: 1-64 letters, digits, <code>_</code> or <code>-</code> . Its tools are reached as <code>peter\$mcp\$<name>\$<tool>()</code> inside the <code>r</code> tool.
<code>command, args</code>	The program and its arguments for a <code>stdio</code> server.
<code>url</code>	The endpoint of a Streamable HTTP server.
<code>env, headers</code>	Named character vectors: environment variables of a <code>stdio</code> server, HTTP headers of an HTTP server. Write secrets as <code>\${VAR}</code> placeholders.
<code>exposure</code>	How the model reaches the tools: <code>"r"</code> (R functions listed in the prompt), <code>"direct"</code> (declared as tools), <code>"deferred"</code> (found through <code>peter\$search()</code>) or <code>"hidden"</code> .
<code>timeout</code>	Seconds per request; progress notifications from the server extend it.
<code>scope</code>	<code>"user"</code> (default) or <code>"project"</code> .

Value

`gptr_mcp_add()` returns the server spec invisibly; `gptr_mcp_remove()` returns `TRUE` invisibly when a server was removed, else `FALSE`.

Examples

```
proj = tempfile("proj")
dir.create(proj)
old = options(gptr.project_root = proj)
gptr_init(proj)
gptr_mcp_add("fs", command = "npx",
            args = c("-y", "@modelcontextprotocol/server-filesystem", "."),
            scope = "project")
gptr_mcp_remove("fs", scope = "project")
options(old)
unlink(proj, recursive = TRUE)
```

gptr_mcp_serve

Serve the live R session to other agents over MCP

Description

Starts an MCP server inside this R session that offers `r`, `read`, `edit` and `write` to agents such as Codex, Claude Code, Claude Desktop or Cursor. It listens only on 127.0.0.1, requires a 192-bit bearer token, rejects foreign browser origins, and runs every call through your permission settings; R code evaluates in `envir`, where its objects persist. The calls belong to a dedicated `gptr` session whose permission mode is the one in effect when the server starts (stop and start the server to change it); like any new session, it becomes `gptr_last()`. Requests are answered while R waits at the console or inside a `gptr` call; one that needs your approval is refused with a note on how to allow it, because `gptr` never asks from a background callback. The token appears only in the snippets of `$config` (printed redacted; `as.character()` gives the text to paste; `$config$codex` holds the codex options in `$args` and the environment to start Codex with in `$env`) and in the environment of children `gptr` starts. One server runs per R process. Needs `'httpuv'`, `'later'` and `'openssl'`.

Usage

```
gptr_mcp_serve(
  tools = c("r", "read", "edit", "write"),
  envir = parent.frame(),
  port = NULL,
  stop = FALSE
)
```

Arguments

<code>tools</code>	The tools to serve: a subset of <code>c("r", "read", "edit", "write")</code> .
<code>envir</code>	Where served R code evaluates and its objects persist.
<code>port</code>	A port, or <code>NULL</code> for a free one.
<code>stop</code>	<code>TRUE</code> to stop the server.

Details

If shutdown cannot be confirmed, access is revoked and the server is retained for retry. Call `gptr_mcp_serve(stop = TRUE)` again; new requests are refused until shutdown completes.

Value

A `gptr_mcp_handle` with `$url`, `$port`, `$token_env`, `$config` and `$stop()`; calling again returns the running handle; with `stop = TRUE`, `invisible(NULL)`.

Examples

```
if (interactive() && rlang::is_installed(c("httpuv", "later", "openssl"))) {
  h = gptr_mcp_serve(envir = new.env())
  h$config$codex
  gptr_mcp_serve(stop = TRUE)
}
```

gptr_models	<i>List models from the model catalog</i>
-------------	---

Description

Searches the merged model catalog: the shipped snapshot (models.dev plus gptr’s reviewed prices and capabilities), a refreshed copy in `tools::R_user_dir("gptr", "cache")`, models declared by registered providers, user configuration and discovered local servers. Offline by default: only `refresh = TRUE` touches the network.

Usage

```
gptr_models(query = NULL, provider = NULL, refresh = FALSE)
```

Arguments

query	NULL or a regular expression or alias (for example "sonnet"), matched against the reference, the name and the aliases; the model an alias resolves to is listed first.
provider	NULL or a provider id (for example "anthropic").
refresh	TRUE downloads the current models.dev catalog with ETag revalidation into the user cache. For a local provider (provider = "ollama", "lmstudio", ...) it asks that server for its installed models instead (a 1 second limit per request; for Ollama the native /api/version, /api/tags and /api/show endpoints). Ollama discovery requires a loopback address under the default local-only policy; only an explicit human setting at user or session scope can relax it (see gptr_config()). The only network use of this function; it never starts or installs a server and never downloads a model.

Details

A catalog entry describes a route, not current account access. Copy its ref into the model argument of `peter()` to choose that route. Ollama routes require current installed model evidence before inference; discovery does not pull models. See `vignette("language-models", package = "gptr")` for setup and `gptr_providers()` for credentials and reachability.

Value

A `gptr_models` data frame with columns `ref`, `provider`, `name`, `context`, `max_output`, `input_price`, `output_price` (USD per million tokens, selected for today's date from the available catalog; 0 for verified local inference, NA when unknown), `reasoning`, `aliases` and `status`. Catalog prices can be stale and are not an account quote.

Examples

```
gptr_models("sonnet")
gptr_models(provider = "anthropic")
```

gp _{tr} _on	<i>Listen to a session's events</i>
----------------------	-------------------------------------

Description

Registers a session-scoped hook (rank 0) for one cataloged event (such as `message_end`, `tool_call`, `turn_end`) or a plugin channel containing `:`. The handler is `function(event, ctx)` and returns what the event allows. Forks never copy listeners.

Usage

```
gptr_on(s, event, handler, matcher = NULL)
```

Arguments

s	A session.
event	An event name; Claude and Codex hook names are refused with the gp _{tr} name.
handler	<code>function(event, ctx)</code> .
matcher	NULL, a tool-name glob for tool events, or <code>function(event)</code> returning a flag.

Value

A function of no arguments that removes the hook, invisibly.

Examples

```
session = peter("hi", model = gptr_fake_provider(list("hello")), .run = FALSE)
seen = new.env()
seen$roles = character()
off = gptr_on(session, "message_end", function(event, ctx) {
  seen$roles = c(seen$roles, event$message$role)
  NULL
})
gptr_step(session)
off()
seen$roles
```

gptr_options

Options that control gptr

Description

gptr reads each option with `getOption()` at the moment it needs it, so options set with `options()` take effect at the next call. Options marked *settings* have no default of their own: when unset, the value comes from the settings layers written by `gptr_config()` (session, project `.gptr/settings.json`, user settings). The safety options (`gptr.ui`, `gptr.interactive`, the guards, `gptr.noninteractive_ask`, `gptr.protect_size`, `gptr.mode` and `gptr.unsafe_no_permissions`) are copied when a run starts, so code that the model runs cannot change them for that run.

Interaction and output

- `gptr.quiet` (logical, FALSE): silence notices and progress messages.
- `gptr.interactive` (logical or NULL, NULL): force the decision whether a person is present to answer questions and permission prompts. This does not supply a UI or an answer in an unattended process.
- `gptr.verbose` (integer or NULL, NULL): 0 silent, 1 progress on stderr (stdout in an ordinary IRkernel cell), 2 the streamed console, 3 debugging; NULL chooses by context (0 in knitr and testthat, 1 under Rscript, 2 at the console).
- `gptr.ui` (character, UI spec or NULL, NULL): the user-interface backend; NULL means the console when a person is present, else none.
- `gptr.history` (logical, TRUE): add console inputs to the R history.
- `gptr.deprecations` (character, "warn"): "warn" or "error" for deprecated calls.

Settings, models and replay

- `gptr.model`, `gptr.mode`, `gptr.preset`, `gptr.system1`, `gptr.small_model` (character or NULL, *settings*): the option layer of the settings of the same names.
- `gptr.project_root` (character or NULL, NULL): the project root; also the environment variable `GPTR_PROJECT_ROOT`.
- `gptr.replay` (character or NULL, *settings*, "auto"): how recorded document blocks are used: "auto", "replay", "live" or "record"; the replay argument of `peter()` wins.

- `gptr.record` (character or NULL, *settings*, "ask"): whether gptr may write into documents: "auto", "ask" or "off".
- `gptr.interpolate` (logical, TRUE): {*identifier*} interpolation in literal prompts.

Sessions, turns and values

- `gptr.max_turns` (integer, 50): turns per programmatic run.
- `gptr.max_turns_console` (integer, 200): turns per console prompt.
- `gptr.max_nested_calls` (integer, 20): `peter()` calls per evaluation of model code.
- `gptr.value_copy_max` (bytes, 1048576): designated result values below this size are copied; larger ones are kept by name.
- `gptr.values_max_bytes` (bytes, 67108864): value copies held per session.
- `gptr.background_tools` (character, "idle"): "idle" or "wait" for experimental background sessions.
- `gptr.out_keep` (integer, 20): results kept per session for `peter$out()`.
- `gptr.spill_days` (number, 7): age in days after which spill files are pruned.

Concurrency and sub-agents

- `gptr.max_active` (integer, 8): concurrent HTTP transfers.
- `gptr.subagents.max_active` (integer, 8): concurrent inline sub-agents; the default of `gptr_parallel()`'s `max_active`.
- `gptr.subagents.max_cli` (integer, 4): concurrent command-line sub-agents.
- `gptr.subagents.max_workers` (integer or NULL, NULL): worker processes; NULL means `min(4, cores - 1)`. Under R CMD check every pool of child processes is capped at 2.
- `gptr.subagents.max_tasks` (integer, 8): children per team or fan-out started by model code.
- `gptr.subagents.max_depth` (integer, 1): nesting depth of child sessions (at most 2).
- `gptr.child_text_max` (bytes, 51200): text returned per child task.

Transport and processes

- `gptr.connect_timeout` (seconds, 20), `gptr.first_byte_timeout` (seconds, 120) and `gptr.idle_timeout` (seconds, 90): network timeouts.
- `gptr.max_retry_delay` (seconds, 60): a longer retry-after from a provider fails at once.
- `gptr.max_attempts` (integer, 4): transport attempts per request.
- `gptr.wire_log` (logical or path, FALSE): write a redacted log of every request and response inside the workspace or the session temporary directory.
- `gptr.supervise` (logical or NULL, NULL): supervise child processes; NULL means yes except under R CMD check.
- `gptr.stdin_timeout` (seconds, 60): time allowed to write pending input to a child.
- `gptr.cli_path` (named list or NULL, NULL): explicit paths of the claude and codex command-line tools.
- `gptr.cli_turn_timeout` (seconds, 3600): wall-clock time per command-line turn.

Evaluation and tools

- `gptr.r_timeout` (seconds, 3600): time limit of the `r` tool when nobody is present.
- `gptr.r_output_tokens` (integer, 4000): estimated tokens of one `r` result.
- `gptr.r_max_images` (integer, 3): plot images attached to one `r` result.
- `gptr.helper_output_tokens` (integer, 1500): printed size of `peter$ helper` results.
- `gptr.read_max_tokens` (integer, 12000): size cap of the `read` tool.
- `gptr.plot_width`, `gptr.plot_height`, `gptr.plot_res` (integers, 768, 512, 120): plots sent to the model.

Permissions

- `gptr.noninteractive_ask` (character, "stop"): what a permission question does when nobody can answer: "stop" ends the run with status blocked and a `gptr_error_permission` condition; "deny" returns a denial to the model.
- `gptr.critical_guard` (logical, TRUE): level-4 actions ask even in auto mode.
- `gptr.secret_guard` (logical, TRUE): reads of registered secrets ask even in auto mode.
- `gptr.protect_size` (bytes, 1e8): overwriting a larger object is a level-3 action.
- `gptr.plan_handoff` (logical, TRUE): hand a plan from plan mode to the next call.
- `gptr.unsafe_no_permissions` (logical, FALSE): turns the permission gate off entirely; honored only when set outside a run, for sandboxed continuous integration.

Context, caching and compaction

- `gptr.compact_at` (tokens or NULL, 200000): the compaction soft cap; NULL disables the cap.
- `gptr.compact_cold_min` (tokens, 100000): the size above which a cold cache compacts.
- `gptr.cache_ttl` (character, "gap"): prompt-cache lifetime policy: "gap", "5m" or "1h".
- `gptr.cache_gap` (seconds, 240): a pause between requests longer than this switches the cache lifetime to one hour.
- `gptr.check_prefix` (character, "event"): what a broken cache prefix does: "event", "warn" or "error".
- `gptr.skills_budget` (integer, 1500) and `gptr.mcp_budget` (integer, 1500): tokens of the skill and MCP tool catalogs.

Checkpoints and undo

- `gptr.checkpoint` (character, "on"): "on", "files" or "off".
- `gptr.undo_capture_max` (bytes, 1e8): objects up to this size are captured by reference before a change, even when the change was not predicted.
- `gptr.undo_max_bytes` (bytes, 1e9): object images held in memory per session.
- `gptr.undo_spill_max` (bytes, 2e9): the largest object image written to disk.
- `gptr.undo_turns` (integer, 20): object images older than this many turns are dropped.
- `gptr.checkpoint_disk_bytes` (bytes, 2e9), `gptr.checkpoint_days` (days, 30) and `gptr.checkpoint_turns` (integer, 100): retention of the checkpoint store.

- `gptr.checkpoint_track_file_max` (bytes, 1e6) and `gptr.checkpoint_track_total` (bytes, 1e8): the per-file and total size of tracked project files.
- `gptr.checkpoint_capture_max` (bytes, 5e7): a larger changed file gets no stored copy.
- `gptr.checkpoint_scan_budget` (seconds, 0.25): above this walk time the project is scanned once per turn.
- `gptr.checkpoint_rng` (logical, TRUE): report changes of the random-number state in the rewind report (gptr never changes your random seed).
- `gptr.checkpoint_close_devices` (logical, FALSE): close graphics devices opened by an undone turn.

Secrets

- `gptr.redact_min_chars` (integer, 8): the shortest secret value that is redacted.
- `gptr.redact_patterns` (logical, TRUE): also redact text that looks like a key; known values are always redacted.
- `gptr.stream_hold_max` (integer, 4096): characters held back while redacting a stream.
- `gptr.env_export` (logical, TRUE): the default of `gptr_env(set_env=)`.
- `gptr.prompt_secrets` (character, "redact"): secret-looking text in prompts: "redact" or "ask".

System 1

- `gptr.s1_max_active` (integer, 8): concurrent System 1 requests.
- `gptr.s1_rounds` (integer, 3): retry rounds for failed elements.
- `gptr.s1_state_max` (integer, 2000): characters of a session's state sent to System 1.
- `gptr.s1_max_elements` (integer, 10000): elements per System 1 call.

Documents, MCP and artifacts

- `gptr.doc_output_lines` (integer, 12): output lines recorded per execution.
- `gptr.doc_source_frames` (logical, TRUE): let gptr find the calling line of a script run with `source()`.
- `gptr.mcp_timeout` (seconds, 60) and `gptr.mcp_probe_timeout` (seconds, 5): MCP request and protocol-probe time limits.
- `gptr.mcp_debug` (logical, FALSE): keep redacted MCP server logs in the user cache.
- `gptr.artifact_max_bytes` (bytes, 5e8): the largest artifact data snapshot.

Environment variables

- `GPTR_REPLAY`: the replay mode below the `gptr.replay` option; `GPTR_REPLAY=replay` proves that a script makes no model calls.
- `GPTR_PROJECT_ROOT`: overrides the project root, like `gptr.project_root`.
- `ANTHROPIC_API_KEY`, `OPENAI_API_KEY`, `GEMINI_API_KEY`, `TYPESAFE_API_KEY` and the other provider keys: read at the first use of a provider; see [gptr_env\(\)](#) for `.env` files.

- GPTR_WORKER, GPTR_SUBAGENT_DEPTH and GPTR_MCP_TOKEN: set by gp^{tr} in its own child processes only.
- GPTR_LIVE_TESTS: "true" enables the package's live tests; not used at run time.
- _R_CHECK_PACKAGE_NAME_: set by R CMD check; outside the package's own tests gp^{tr} then replays recorded document blocks only and caps each child-process pool at two.

See Also

[gp^{tr}_config\(\)](#) for settings stored in files, [gp^{tr}_security](#) and [gp^{tr}_egress](#); [vignette\("configuration", package = "gp^{tr}"\)](#) for scope, precedence and grouped examples.

gp ^{tr} _parallel	<i>Run several agent calls concurrently</i>
----------------------------	---

Description

Each argument is a [peter\(\)](#) call; it is evaluated with deferral on, so it builds its session without running it, and all members then run together on one reactor, at most `max_active` at a time. The result is a team session: `team$text` joins the members' answers under `### <name> (<model>)` headings, `team$value` is the named list of their values, and `team$<name>` (or `team[[i]]`) is a member's session. Piping the team into [peter\(\)](#) continues it.

Usage

```
gptr_parallel(
  ...,
  .list = NULL,
  max_active = NULL,
  on_error = c("return", "stop")
)
```

Arguments

<code>...</code>	Named peter() calls (or sessions created with <code>.run = FALSE</code>).
<code>.list</code>	A named list of sessions created with <code>.run = FALSE</code> .
<code>max_active</code>	The number of members that run at once; NULL uses the option <code>gp^{tr}.subagents.max_active</code> (8).
<code>on_error</code>	"return" keeps failed members with their status; "stop" signals the first failed member's condition once every member settled.

Details

Members evaluate R code in their own environment (`envir =`) with their own random-number stream, and share one budget, as one `peter()` call does. A member's `tools =`, `budget =` and the run options in its `.opts` (such as `max_turns`) are not applied.

Use `peter(..., agents = list(...))` for named roles on one task, or `parallel =` for one task per input element. Those routes start new foreground children and cannot be deferred as members here. A team report is model-generated output; inspect child statuses and workspace results before continuing the team with a synthesis prompt.

Value

A team session (`kind = "team"`).

Examples

```
fake = gptr_fake_provider(list("ok"))
session = gptr_parallel(planner = peter("Plan it", model = fake),
                        review = peter("Review it", model = fake))
names(session$children)
```

gptr_permissions	<i>Manage permission rules</i>
------------------	--------------------------------

Description

Lists the permission rules in effect, or adds and removes rules. A rule is `tool` or `tool(spec)`: a path glob for `read`, `write`, `edit`, `grep`, `find` and `ls` (`write(results/**)`, relative to the project root; `~/...` for the home; `//...` for other absolute paths); for `r`, `level<=n`, `fn:name,...` (every flagged function covered), `category:name,...`, `sh:<command glob>(r(sh:git status*))`, `sql:<keywords>(r(sql:select))` and `secret:NAME` (the only rule that pre-approves a guarded secret read); MCP tools by name (`mcp__github__*`). Deny rules win over ask rules, which win over allow rules. Allow rules never loosen plan mode and never pre-approve level-4 (critical or control) actions.

Usage

```
gptr_permissions(
  allow = NULL,
  ask = NULL,
  deny = NULL,
  remove = NULL,
  scope = c("session", "project", "user")
)
```

Arguments

- allow, ask, deny Character vectors of rules to add to that list, or NULL.
- remove Character vector of rules to remove from every list of scope, or NULL.
- scope One of "session", "project", "user".

Details

Scopes: "session" is this R process; "project" is the user-level project file `tools::R_user_dir("gptr", "config")/project`, personal and never inside the project tree; "user" is the user settings file. The listing also shows the shared project rules of `.gptr/settings.json` (an untrusted project contributes only deny and ask rules) and the deny/ask rules of a legacy `.gptr/settings.local.json` in a trusted project.

Called from model code during a run, adding or removing rules needs the user's approval of that call; otherwise it signals `gptr_error_permission`.

Value

A `gptr_permissions` data frame with columns `rule`, `list`, `scope` and `source`; invisibly when rules were added or removed.

Examples

```
gptr_permissions(allow = "r(level<=1)")
gptr_permissions()
gptr_permissions(remove = "r(level<=1)")
```

gptr_plugins	<i>Plugins known to this session</i>
--------------	--------------------------------------

Description

Lists the plugins gptr can see: plugins enabled through `peter(plugins = )` or the `plugins` setting (a settings plugin not enabled yet shows as `lazy`), attached packages that ship `inst/gptr/`, the project's `.gptr/plugins/` directories and installed Claude Code plugins. With `installed = TRUE` it also scans every installed package for `inst/gptr/`. Nothing is loaded or run. A plugin enabled both for the process and for a live session is listed once.

Usage

```
gptr_plugins(installed = FALSE)
```

Arguments

- installed TRUE to scan every installed package as well.

Details

Enable a plugin with `peter(plugins = "name")` or the `plugins` configuration setting. Packages put resources in `inst/gptr/`; directory plugins use a root `plugin.json`. R factories activate lazily only when the manifest declares `extension.provides` and does not request eager activation. Claude bundles contribute declarative resources; their hooks and executable plugin behavior are not imported.

Value

A `gptr_plugins` data frame with columns `name`, `version`, `api`, `kind` (package, directory, claude-plugin), `enabled`, `state` (lazy, active, disabled, failed), `provides`, `tokens` and `path`.

See Also

[gptr_check](#), [gptr_reload](#), [gptr_registry](#); `vignette("skills-and-plugins", package = "gptr")` for resource files and plugin manifests.

Examples

```
gptr_plugins(installed = TRUE)
```

`gptr_policy`

Define a permission policy

Description

`check(call, ctx)` sees every tool call before it runs and returns `NULL` (no opinion) or `list(decision = "allow" | "deny" | "ask" | "ask_human" | "modify", reason, input)`. Decisions combine as `deny > ask_human > ask > modify > allow`; only a person answers an `ask_human`, never a hook; a policy that errors denies. Keep checks under 10 ms.

Usage

```
gptr_policy(name, check, description = NULL)
```

Arguments

<code>name</code>	Policy name.
<code>check</code>	<code>function(call, ctx)</code> .
<code>description</code>	One line for listings.

Value

A spec of class `c("gptr_policy", "gptr_spec")`.

Examples

```
gptr_policy("no_installs", check = function(call, ctx) {
  if (identical(call$name, "r") && grepl("install.packages", call$input$code, fixed = TRUE)) {
    list(decision = "deny", reason = "installs are not allowed here")
  } else {
    NULL
  }
})
```

gptr_preimage

Tell the object checkpointer how to capture an object

Description

`gptr_preimage()` is the S3 generic the object checkpointer calls for a binding of the workspace before a tool call that runs R code. It decides how the value the binding holds now is kept, so that a rewind can put it back. Methods are leaf functions: they may read `x` but must never store it anywhere.

Usage

```
gptr_preimage(x, name, ctx, ...)

## Default S3 method:
gptr_preimage(x, name, ctx, ...)

## S3 method for class 'data.table'
gptr_preimage(x, name, ctx, ...)
```

Arguments

<code>x</code>	The object bound to name.
<code>name</code>	The binding name (a string).
<code>ctx</code>	A list: predicted, what the agent's code is predicted to do to name ("assign", "modify", "byref", "remove" or "none"); bytes, the size of <code>x</code> in bytes (NA when unknown); budget, the largest copy allowed, in bytes. When <code>ctx\$dry</code> is TRUE the checkpointer only asks whether a capture is possible and a method must not copy.
<code>...</code>	Unused; for methods.

Details

The default method keeps value-semantics objects by reference ("ref": nothing is copied unless the agent edits the object in place) and reports environments (including R6 and RefClass objects) and external pointers as not restorable ("none"). The `data.table` method returns a deep copy made with `data.table::copy()` ("copy") when the agent's code is predicted to modify the table

by reference (`:=`, `set*`()) and the table fits the budget. Packages add methods for their own classes with a delayed registration, `S3method(gptr::gptr_preimage, myclass)`; an R6 class can, for example, return `x$clone(deep = TRUE)` as "copy". This generic is experimental.

Value

A list with `mode` ("ref", "copy" or "none"), `reason` (a string explaining "none", else NULL) and `copy` (the deep copy for "copy", else NULL).

Examples

```
gptr_preimage(1:3, "x", list(predicted = "assign", bytes = 64, budget = 1e9))$mode
gptr_preimage(new.env(), "cfg", list(predicted = "modify", bytes = NA, budget = 1e9))$reason
```

gptr_prob	<i>Probabilities and confidence of System 1 answers</i>
-----------	---

Description

System 1 calls (`peter(question, x, model = jev)`) return typed vectors: a `gptr_decision` (logical), a `gptr_choice` (character) or a `gptr_score` (double, the expected 0-based level). They work in `if()`, `while()`, `ifelse()`, `table()`, `sum()` and comparisons like the bare vectors, and carry the model's probabilities as attributes. `gptr_prob()` reads them.

Usage

```
gptr_prob(x, what = c("prob", "confidence", "probabilities"))
```

Arguments

<code>x</code>	A System 1 vector: a <code>gptr_decision</code> , <code>gptr_choice</code> or <code>gptr_score</code> .
<code>what</code>	"prob" (decisions: $P(\text{yes})$; choices: the probability of the chosen option; scores: the confidence), "confidence" (decisions: $\text{abs}(2 * p - 1)$) or "probabilities" (a matrix with one row per element and one column per option or level; for decisions the columns FALSE and TRUE).

Details

Probabilities are the model's own; they are empirically calibrated only when the printed footer says calibrated. Native decision models report calibration as unknown unless calibration evidence was recorded, and emulated answers are always uncalibrated. Answers combined from several calls (`c()`, `[<-`, `vctrs::vec_c()`) say calibrated only when every part is calibrated and uncalibrated when any part is uncalibrated. For choices and scores the confidence describes how concentrated the distribution is, not the probability that the answer is correct.

A score can be fractional: with levels low, medium and high (0, 1 and 2), probabilities 0.85, 0.10 and 0.05 give the score 0.20. It is not rounded to the most likely level. `attr(x, "meta")` records the model, engine, calibration state, cached elements, usage and available execution provenance such as locality, model digest and server version.

Value

A named numeric vector, or a matrix for what = "probabilities".

Input shape and uncertainty

Atomic vectors and unnamed lists give one input state per element; data frames give one per row. Fully named lists and I(x) give one structured state. These states can contain the actual input values sent to the provider; see [gptr_egress](#). min_confidence makes low-confidence answers NA by default, including unknown confidence when the minimum is positive. Use isTRUE() in scalar control flow when abstention is possible, and handle uncertain inputs separately.

System 1 options

gptr.s1_max_active (8) concurrent requests, gptr.s1_rounds (3) bounded retry rounds, gptr.s1_state_max (2000) characters of a piped session's state and gptr.s1_max_elements (10000) elements per call.

Examples

```
judge = gptr_fake_provider(list(0.9, 0.2), name = "judge", type = "classifier")
d = peter("Is this about dogs?", c(a = "A puppy.", b = "A car."), model = judge)
gptr_prob(d)
```

gptr_prompt	Show the frozen system prompt, tool array and first message
-------------	---

Description

gptr_prompt() shows what gptr sends before the conversation: the two system blocks (T0, the static sections; T1, the machine and project sections), the tool array and the first user message, with an estimated token count per section. It makes no model call and writes nothing: a preview never consumes a pending plan and queues no message for the model.

Usage

```
gptr_prompt(x = NULL, preset = NULL, tokens = TRUE)

## S3 method for class 'gptr_prompt_view'
print(x, ...)
```

Arguments

x	For gptr_prompt(), a gptr_session (its frozen prompt and first message) or NULL (what a new session would freeze now with the current settings); for print(), a gptr_prompt_view.
preset	NULL or a preset name ("minimal", "standard", "readonly", "extended", or one registered by a plugin or for the session) to preview instead of the frozen or configured one.
tokens	TRUE to add estimated token counts per section.
...	Unused.

Details

For a session, the view shows its frozen blocks (restored from its `gptr.frozen` entry when needed) and the text of its first user message, context blocks included. With `preset`, for a session that has not frozen its prompt yet, or for one whose next run freezes a fresh prompt (resumed from a file of another project or one that git tracks), it composes what would be frozen now.

Value

A `gptr_prompt_view`: a list with `system` (`list(t0, t1)`), `tools_json` (the tool array as JSON text), `first_message` (text), `sections` (data frame name, tier, tokens) and `total_tokens`; the attributes `preset` and `tool_names` name the preset and the declared tools. `print()` shows each part with its token estimate and returns `x` invisibly.

Examples

```
v = gptr_prompt(preset = "minimal")
v$sections
```

<code>gptr_prompt_section</code>	<i>Define a system-prompt section</i>
----------------------------------	---------------------------------------

Description

A section of the frozen system prompt, rendered once per session in ascending order: `T0` sections form the stable prefix, `T1` sections follow. `text` may be a function of `ctx`; `parent` makes the section a fragment of another section.

Usage

```
gptr_prompt_section(
  name,
  text,
  tier = c("T0", "T1"),
  order = 500L,
  budget = 300L,
  parent = NULL
)
```

Arguments

<code>name</code>	Section name (the tag it is wrapped in).
<code>text</code>	A string or <code>function(ctx)</code> returning a string or <code>NULL</code> .
<code>tier</code>	"T0" or "T1".
<code>order</code>	Position among sections.
<code>budget</code>	Token budget of the section.
<code>parent</code>	Name of the section this fragment belongs to, or <code>NULL</code> .

Value

A spec of class `c("gptr_prompt_section", "gptr_spec")`.

Examples

```
gptr_prompt_section("house_rules", "Use SI units in every table.", tier = "T1", order = 780L)
```

gp _{tr} _provider	<i>Define a model provider</i>
----------------------------	--------------------------------

Description

A provider is data: an id, the wire api its adapter implements, a base URL, how to find a credential and its models. auth names environment variables (or is a function returning a secret handle) and is resolved per request.

Usage

```
gptr_provider(  
  id,  
  api,  
  base_url = NULL,  
  auth = NULL,  
  models = NULL,  
  compat = list(),  
  type = c("chat", "classifier", "cli"),  
  headers = list(),  
  discover = NULL,  
  status = NULL,  
  aliases = character(),  
  local = FALSE,  
  offline = FALSE,  
  rate = NULL  
)
```

Arguments

id	Provider id, <code>^[a-z0-9][a-z0-9-]*\$</code> .
api	Wire api (the name of an adapter), for example "openai-completions".
base_url	Endpoint base URL.
auth	Character vector of environment-variable names, a function, or NULL.
models	List of model records (each with at least id).
compat	Named list of compatibility switches for the adapter.
type	"chat", "classifier" (System 1) or "cli".
headers	Named list of non-secret header strings.

discover	function() listing models on request, or NULL.
status	function() reporting cached provider status, or NULL.
aliases	Alternative names of the provider.
local	Endpoint locality hint permitting unknown model ids. Resolved model locality is checked separately: a loopback server may route inference to a remote model.
offline	TRUE when no remote model is called (test providers).
rate	list(requests_per_s, tokens_per_s) static limits, or NULL.

Value

A spec of class `c("gptr_provider", "gptr_spec")`.

Examples

```
gptr_provider("corp", api = "openai-completions", base_url = "https://llm.corp.example/v1",
  auth = "CORP_LLM_KEY", models = list(list(id = "corp-large", context = 128000)))
```

gptr_providers	<i>List the configured model providers</i>
----------------	--

Description

Shows every registered provider record: its wire api, where its credential comes from (as NAME #fingerprint, never the value), the registry source of the record, its status, default model, egress acknowledgment and, for subscription command-line tools, their version.

Usage

```
gptr_providers(check = FALSE, check_login = FALSE)
```

Arguments

check	FALSE (default) performs no network or process input/output unless check_login = TRUE. TRUE also probes each HTTP provider's models endpoint once without credentials (2 s timeout; skipped under R CMD check) and lets command-line providers check their tool; it never sends a paid request.
check_login	Also check Codex and Claude Code's CLI-reported login status using their supported status commands (3 s timeout per subprocess, no model request). Adds a login column: signed in, not signed in, or unknown. Unsupported CLI versions, missing tools and failed checks report unknown; other providers report not applicable. A supported API-key login can count as signed in; this does not verify credentials online or establish subscription billing. Defaults to FALSE.

Details

status is ready, no key, no base url or invalid base url (HTTP providers), disabled (the settings say providers.<id>.enabled: false), error (the provider's settings or its credential lookup failed) or what a command-line provider reports; with check = TRUE the ready or no key of an HTTP provider becomes reachable (HTTP <code>) for a reachable endpoint (a 401 without a key still proves reachability), otherwise unreachable, or not checked under R CMD check. egress is ack when no acknowledgment is needed (offline providers, local servers at a loopback address) or the user has given it. Listing reads credentials only: it never registers an environment variable or binds it to a provider.

ready means the required configuration is present; it does not validate the credential, account quota or access to a specific model. check = TRUE tests reachability, not login. See vignette("language-models", package = "gptr") for API, command-line and local setup.

Value

A gptr_providers data frame with columns id, type, api, credential, source, status, default_model, egress (ack or needed) and version, plus login when check_login = TRUE.

Examples

```
gptr_providers()
```

gptr_redact

Redact secrets from text or from a nested list

Description

Replaces the values of registered secrets (and their URL-encoded, JSON-escaped and base64 forms) with markers such as [secret:TYPESAFE_API_KEY] and, except for the user_data profile, applies the pattern layer (provider key shapes, bearer tokens, URL passwords, private keys, NAME=value lines). gptr applies the same redactor at every sink; plugins and users call it for their own logs. Redaction is idempotent and never fails on invalid UTF-8 (it then matches byte-wise). Opaque replay fields of messages (signatures, encrypted reasoning) are never modified.

Usage

```
gptr_redact(
  x,
  profile = c("persist", "stream", "context", "code", "user_data")
)
```

Arguments

x	A character vector, or a list (redacted recursively).
profile	The sink profile: "persist" (files), "stream" (console and events), "context" (text sent to a model), "code" (R code for a history document: a string literal whose value is a registered secret becomes Sys.getenv("NAME")) or "user_data" (registered values only).

Value

x with secrets replaced by markers; the same type and attributes as x.

Options

gptr.redact_min_chars (8): shortest value that is value-redacted. gptr.redact_patterns (TRUE): the pattern layer; values are always redacted. gptr.stream_hold_max (4096): streaming hold-back cap in characters. gptr.env_export (TRUE): default of gptr_env(set_env =). gptr.prompt_secrets ("redact"): secret-looking text in prompts, "redact" or "ask". gptr.secret_guard (TRUE): guarded secret reads ask even in auto mode.

Examples

```
gptr_redact("Authorization: Bearer abcdef0123456789abcdef")
gptr_redact(list(note = "db at postgres://analyst:hunter2x@db.example.test/prod"))
```

gptr_register	<i>Register a capability spec</i>
---------------	-----------------------------------

Description

Registers a spec made by `gptr_spec()` or one of the spec constructors at top level: rank 3, source "user", for the lifetime of the R process. Sessions frozen before the call are not changed; the next session sees the record. A user record overrides a built-in record of the same kind and name only (the built-in's other records keep working).

Usage

```
gptr_register(spec)
```

Arguments

spec A spec (class gptr_spec).

Details

Called from model code while a run executes a tool, `gptr_register()` and the function it returns signal `gptr_error_permission` unless the user approved that call.

Value

A function that removes the record again, invisibly.

Examples

```
off = gptr_register(gptr_command("hello", function(args, ctx) "hi"))
off()
```

gptr_registry	List the extension registry
---------------	-----------------------------

Description

One row per process-level record (session-scoped records are not listed): its kind, name, source (builtin:<name>, plugin:<name>, user, project), rank, state (lazy, active, overridden, disabled), the estimated tokens its declaration costs, and whether the kind is experimental. With diagnostics = TRUE, the redacted diagnostics log instead.

Usage

```
gptr_registry(kind = NULL, diagnostics = FALSE)
```

Arguments

- kind NULL for every kind, or a character vector of kind names.
- diagnostics TRUE to return the diagnostics log.

Value

A gptr_registry data frame (columns kind, name, source, rank, state, tokens, experimental), or a gptr_diagnostics data frame (columns time, source, event, class, message).

Examples

```
gptr_registry("tool")
gptr_registry(diagnostics = TRUE)
```

gptr_reload	Reload extensions
-------------	-------------------

Description

Bumps the registry generation, so that extension API objects captured by old code signal gptr_error_stale_api, and re-declares lazily activated plugins from their manifests (their factories run again on first use). Discovery of declarative resources (skills, prompts, agents, MCP configurations, plugin manifests) is keyed on the generation, so it runs again on next use. Sessions whose prompt is already frozen are not changed. Refused from model code while a run executes a tool, unless the user approved that call.

Usage

```
gptr_reload()
```

Value

The new registry generation (an integer), invisibly.

Examples

```
gptr_reload()
```

gptr_return

Designate the result of an agent run

Description

Called by R code the agent runs (or by you inside a tool) to designate the run's result, which the session then returns as `$value`. Objects bound in the session's workspace are kept by name when large (no copy), copied when small; other values are boxed. Outside a run it returns its argument invisibly and does nothing else, so recorded code that still contains the call runs cleanly.

Usage

```
gptr_return(x)
```

Arguments

`x` The value; a bare name is recorded by name.

Value

NULL invisibly during a run; `x` invisibly outside a run.

Examples

```
y = gptr_return(1:3)
y
```

gp _{tr} _rewind	<i>Rewind a session: undo turns, restore objects and files, move the conversation</i>
--------------------------	---

Description

gp_{tr}_rewind() is a branch-in-place on the one session object: it undoes the checkpoint records of the turns being left (newest first), redoes the records of a target on another branch (oldest first) and appends one gp_{tr}.rewind entry parented at the target (the session file stays append-only and the rewind survives a reload). It hands back the undone prompt in s\$editor_text and returns s invisibly, so it pipes: session |> gp_{tr}_rewind() |> peter("Try another way"). Use gp_{tr}_fork() for a second session.

gp_{tr}_checkpoints() lists one row per turn of the active path (all = TRUE adds the turns of abandoned branches): turn; id, the last entry of the turn (pass it as to to gp_{tr}_rewind()); time, when the prompt was sent; prompt (its first 60 characters); objects and files, "changed/restorable" counts; held_mb and disk_mb, megabytes of object pre-images held in memory and on disk; and branch ("active" or "abandoned").

Usage

```
gptr_rewind(
  s,
  turn = -1L,
  to = NULL,
  restore = c("all", "conversation", "workspace"),
  force = FALSE,
  preview = FALSE
)
```

```
gptr_checkpoints(s, all = FALSE)
```

Arguments

s	A gp _{tr} _session.
turn	Integer. Negative counts back from the last turn (-1 undoes the last turn); 0 goes back to before the first turn; k > 0 keeps turns 1..k of the active path.
to	An entry id from gp _{tr} _checkpoints(s, all = TRUE); overrides turn. Any entry works, including the end of an abandoned branch, which is how redo works.
restore	"all" (objects, files, session state and the conversation), "conversation" (only the conversation) or "workspace" (only objects, files and session state; the conversation stays where it is).
force	Also restore items that changed after the checkpoint (3-way conflicts).
preview	Return the plan instead: a data frame with one row per item (record, turn, action, checkpointer, item, restore, reason); nothing changes.
all	Also list the turns of abandoned branches.

Details

Restores are 3-way: an object or file that changed after the turn (by you or another session) is kept and reported, unless `force = TRUE`. Reference objects (environments, R6, external pointers), objects over the undo budget, environment variables, loaded namespaces, the random-number state and effects outside R (network, databases, processes) are not restored. Items that were not restored are listed in `s$last_rewind$report` and raise the warning `gptr_warning_rewind_partial`. Files outside the project and `tempdir()` are restored only after you confirm each path. After a full restore the model is told nothing (the next request's prefix is byte-identical to the earlier request at the target); after a partial one the next prompt carries a short `<rewind>` block listing what was not restored. Model code may rewind another session only when you approve that call.

Value

`gptr_rewind()` returns `s`, invisibly (the plan when `preview = TRUE`); `s$last_rewind` holds the report and `s$editor_text` the undone prompt. `gptr_checkpoints()` returns a `gptr_checkpoints` data frame (it prints at most 20 rows).

Options

Options of checkpoints and rewind (`?gptr_options` collects every option):

- `gptr.checkpoint ("on")`: "files" checkpoints files only, "off" nothing (also the settings key checkpoint).
- `gptr.undo_capture_max (1e8)`: bytes; objects up to this size are captured by reference.
- `gptr.undo_max_bytes (1e9)`: bytes of pre-images held in memory per session.
- `gptr.undo_spill_max (2e9)`: bytes; the largest object image written to disk.
- `gptr.undo_turns (20)`: object images older than this many turns are dropped.
- `gptr.checkpoint_disk_bytes (2e9)`: bytes of blobs and spilled images before a notice.
- `gptr.checkpoint_days (30)`: unreferenced blobs older than this many days are deleted.
- `gptr.checkpoint_turns (100)`: file checkpoints older than this many turns are not restored.
- `gptr.checkpoint_track_file_max (1e6)`, `gptr.checkpoint_track_total (1e8)`: bytes per file and in all of the baseline taken at the first mutating call.
- `gptr.checkpoint_capture_max (5e7)`: bytes; a larger changed file gets no stored copy.
- `gptr.checkpoint_scan_budget (0.25)`: seconds; slower walks switch to one scan per turn.
- `gptr.checkpoint_rng (TRUE)`: report changes of the random-number state.
- `gptr.checkpoint_close_devices (FALSE)`: close graphics devices an undone turn opened.

Examples

```
d = tempfile("project")
dir.create(d)
op = options(gptr.project_root = d)
fake = gptr_fake_provider(list(
  list(tool = "r", input = list(code = "x = 1")), "Made x.",
  list(tool = "r", input = list(code = "x = x + 1")), "Added one.))
work = new.env()
```

```

session = peter("Make x", model = fake, mode = auto, envir = work)
session |> peter("Add one to x")
work$x
session |> gptr_rewind()
work$x
session$editor_text
gptr_checkpoints(session, all = TRUE)
options(op)

```

gp_{tr}_risk*Classify the risk of R code without running it***Description**

gp_{tr}_risk() is the advisory static classifier behind gp_{tr}'s permission prompts. It reads code without evaluating it and labels each effect it can see with a level from 0 (known read-only) to 4 (critical) and a category (read, object_write, file_write, file_delete, network, process, install, dynamic, session, secret, interactive, critical, control, plus unlisted for functions the risk tables do not list). Level 0 is only what the tables know to be read-only; code whose function is computed at run time is level 3. It cannot see S4 methods, compiled code, package load hooks or the files source() reads: it decides when gp_{tr} asks you, it is not a security boundary.

Usage

```
gptr_risk(code, envir = NULL, root = NULL)
```

Arguments

code	R code: a character vector, a call or an expression.
envir	NULL or the environment the code would run in. When given, assignments to existing bindings are reported as overwrites with their size (object.size() in a leaf; promises and active bindings are never forced) and user-defined functions called by the code are classified through their bodies.
root	The project root used for path classes; NULL means the current project root.

Details

Paths are classified relative to root (workspace, temp, outside, protected, control, instructions, critical, url, wildcard, unknown). Calls of peter\$sh(), system(), system2() and processx::run() with literal commands are classified with the command table (inst/extdata/risk-commands.csv), peter\$sql() by its statements and peter\$py() by a token scan. Plugins and users extend both tables with risk_rule records.

Value

A gp_{tr}_risk object: a list with level (integer 0-4), label, categories, flagged (a data frame with columns call, fn, level, category, path, path_class), paths, secret, secret_guard, assigned, dynamic, and the additive fields sizes (bytes of overwritten objects, by name), secrets (guarded secret names), kind and parse_error.

Examples

```
gptr_risk("unlink('data', recursive = TRUE)")$level
gptr_risk("summary(mtcars)")
e = new.env()
e$df = data.frame(a = 1:3)
gptr_risk("df = head(df, 2)", envir = e)$flagged
```

gptr_router

Define a model router

Description

A router is a virtual model: `route(request, ctx)` runs before every request of a session whose model is the router's name and returns a model reference, or `list(model, thinking = NULL, state = NULL)`. A router that errors or exceeds timeout falls back to the default model.

Usage

```
gptr_router(name, route, description = NULL, timeout = 2)
```

Arguments

name	Router name, usable as <code>model = <name></code> .
route	<code>function(request, ctx)</code> .
description	One line for listings.
timeout	Seconds allowed per call.

Value

A spec of class `c("gptr_router", "gptr_spec")`.

Examples

```
gptr_router("cheapest", route = function(request, ctx) "anthropic/claude-haiku-4-5")
```

gptr_scrub*Find, and optionally remove, registered secrets in persisted files*

Description

Secrets are redacted when they enter a transcript, a cache or a document, but a value that reached a file before it was registered (for example a key pasted into a prompt and only later loaded with `gptr_env()`) stays there. `gptr_scrub()` scans persisted files for the values of every registered secret and their derived forms and reports where they occur. With `dry_run = FALSE` it rewrites those files, replacing each occurrence with a `[secret:NAME]` marker; this is the only sanctioned rewrite of append-only session files, each of which then gets a `gptr.scrub` entry. A key that reached a model or a commit must still be rotated.

Usage

```
gptr_scrub(paths = NULL, dry_run = TRUE, error = FALSE)
```

Arguments

<code>paths</code>	NULL for the workspace's sessions, caches, spill files, plans, transcripts and safe relative document paths bound in this project. An explicit character vector of files and directories overrides that scope; directory traversal stays within each root. Binary files and files with existing writer locks (including stale locks) are reported but not rewritten.
<code>dry_run</code>	If TRUE (the default), only report; if FALSE, rewrite the files.
<code>error</code>	If TRUE, signal an error of class <code>gptr_error_secret_found</code> when any file contains a registered secret (for pre-commit hooks and CI).

Value

A data frame with columns `file`, `secret` (the variable name) and `count`; never values. Returned visibly for a dry run, invisibly after a rewrite.

Examples

```
d = tempfile("proj")
dir.create(d)
writeLines("nothing secret here", file.path(d, "notes.txt"))
gptr_scrub(d)
```

Description

gp_{tr} runs a language model agent inside your R session. The agent reads files, writes files, evaluates R code written by the model in the environment you give it and starts processes on your behalf. This page describes what gp_{tr} does to keep those actions under your control and where its protections end. [gp_{tr}_egress](#) describes what is sent to model providers.

Everything happens because you asked

Nothing runs when the package is loaded. A model is contacted only when you call [peter\(\)](#) (or a function that you give a prompt), and model-written code is evaluated only in the environment you pass as `envir` (by default the frame that called [peter\(\)](#)); gp_{tr} never assigns into the global environment by itself. Files are written only inside a `.gptr/` directory you created with [gp_{tr}_init\(\)](#) or confirmed interactively, inside `tools::R_user_dir("gptr")`, inside the session temporary directory, into documents you bound with [gp_{tr}_doc\(\)](#) or confirmed, and by tool calls that the permission mode allowed. In a non-interactive run without such consent nothing is written outside the session temporary directory.

Permission modes

Every tool call passes a permission gate. The default mode is manual: only actions that the classifier knows to be read-only run without asking; every other action, including any change to a file or an object, asks first with a one-line prompt. `edit` also allows file edits inside the project and still asks before R code that is not known to be read-only; `auto` asks only for level-4 actions (for example deleting the project directory, or changing gp_{tr}'s own configuration) and for reads of registered secrets; `plan` changes nothing. When nobody can answer a question (Rscript, knitr, a scheduled job) the run stops with status blocked and a `gptr_error_permission` condition that says how to allow the action, unless you set `options(gptr.noninteractive_ask = "deny")`. Model code cannot switch the gate off or loosen it during a run: the safety options are copied when the run starts. Only the option `gptr.unsafe_no_permissions`, set by you outside a run, removes the gate, and it is meant for disposable sandboxes.

What the gate cannot do

The risk levels come from a static classifier ([gp_{tr}_risk\(\)](#)). It is advisory and it is not a security boundary: R code can compute function names, call compiled code or load packages whose effects the classifier cannot see, and R has no sandbox for code that runs inside your session. In `auto` mode a model can delete or overwrite files and objects. Use `auto` only in projects you can restore (version control, backups, [gp_{tr}_rewind\(\)](#) for recent turns), and run untrusted prompts or untrusted projects in a disposable container or virtual machine.

Sub-agents, workers and child processes

Inline sub-agents run in your session and see its objects. The worker backend runs a sub-agent in a separate R process that starts from gp_{tr}'s reduced child environment (it does not read your

~/ .Renvi_{ron}), but that process runs under your user account with your file permissions: the worker backend is not an isolation boundary. Its permission requests are sent to your session and classified again there. MCP servers, the claude and codex command-line tools, shell commands started with `peter$sh()` and Shiny artifacts are ordinary processes of your account as well; artifacts start without any registered secret and listen on the loopback interface, and each launch gets an access token in its address (on Windows only when 'openssl' is installed; otherwise gp_{tr} says that the artifact has no token).

Untrusted content

Model replies, tool results, file contents, MCP results and project instruction files (AGENTS.md, CLAUDE.md, .gp_{tr}/vignette.Rmd) are treated as data. Text from these sources is never used as a formatting template, so braces in a reply cannot run R code. A project you cloned is untrusted until you trust it with `gptr_trust(trust = TRUE)` (see `gptr_trust()`), or answer yes when `gptr_init()` asks: until then its settings can only tighten permissions, its extensions, plugins and MCP servers do not run, and its instruction files are shown to the model as information rather than commands. When trusted files change after a pull, gp_{tr} asks again.

Secrets

Keys are held in a private vault and appear in sessions, logs and errors only as markers such as [secret:ANTHROPIC_API_KEY]. Values are redacted before anything is written or sent: the session files, documents, caches, spill files, wire logs and the output of child processes. gp_{tr} never reads the credential files of other tools. Reading a registered secret from model code asks even in auto mode. A key registered after it already appeared in a file (for example pasted into a prompt) can be removed from the files with `gptr_scrub()`; run `gptr_scrub(error = TRUE)` before committing to fail when any registered secret remains.

Data at rest and protected health information (PHI)

gp_{tr} keeps what it needs to resume and replay work. Review what you commit when the data are personal or clinical:

- .gp_{tr}/sessions/ (full conversations, including printed results) is excluded from git by the .gp_{tr}/.gitignore that `gptr_init()` writes.
- .gp_{tr}/cache/s1/ holds System 1 answers and is committed by default so that a script replays without model calls. It stores a salted hash of each input and a hash of each question, never their text, but the answers themselves (a label and its probability) remain, and the salt is committed with the cache, so anyone with the repository can test guesses of short inputs. For PHI, stop committing it with `gptr_config(cache_commit = list(s1 = FALSE, s2 = FALSE), .scope = "project")` (gp_{tr} then keeps a .gitignore in cache/s1/), or clear it with `gptr_cache("clear", "s1")` before committing.
- .gp_{tr}/cache/s2/ (answer text for replay), .gp_{tr}/transcripts/ (console transcripts), .gp_{tr}/checkpoints/ (pre-images of objects and files) and the data snapshots of artifacts (.gp_{tr}/artifacts/<id>/v<n>/data/) are excluded from git by default.
- .gp_{tr}/plans/ (plans proposed in plan mode) and the app.R of each artifact are committed by default; they can quote data values the model saw.
- Documents you record into keep the model's code and up to `gptr.doc_output_lines` lines of printed output per step, which can contain data values. Review them before sharing.

Local servers

`gptr_mcp_serve()` exposes the live session to other agents over HTTP on 127.0.0.1 only, with a random bearer token and an Origin check, and every call passes the permission gate. Any local process that learns the token can call the served tools while the server runs; stop it with `gptr_mcp_serve(stop = TRUE)` when you are done.

See Also

`gptr_egress`, `gptr_options`, `gptr_permissions()`, `gptr_trust()`, `gptr_scrub()`, `gptr_risk()`.

<code>gptr_sessions</code>	<i>Stored and live sessions</i>
----------------------------	---------------------------------

Description

`gptr_sessions()` lists the sessions of the workspace store (`.gptr/sessions/`, or `tempdir()/gptr/sessions/` without a workspace), newest first. It reads only the header and the last lines of each file.

`gptr_resume()` returns the live object when one exists in this process; otherwise it rebuilds the session from its JSONL file (leaf = the last entry; status `idle` when the tail is a final answer, else `interrupted`) with home `envir`. A rebuilt fork always gets a fresh overlay of `envir`. A detached copy (from `saveRDS()`, a knitr cache or `callr`) is attached under the split-brain rules. `block =` returns the session that a document replay bound to that block. Resuming restores conversation state, not a complete analysis workspace, and does not rerun the R tool code. Make required objects available in `envir`; use document replay when the intention is to execute the recorded analysis again.

`gptr_last()` returns the most recently active session of this R process. It is held strongly (it survives `gc()`), so a session whose call was interrupted before its result was assigned is not lost.

Usage

```
gptr_sessions(project = TRUE)
```

```
gptr_resume(x = NULL, envir = parent.frame(), block = NULL, child = NULL)
```

```
gptr_last()
```

Arguments

<code>project</code>	TRUE: the stored sessions; FALSE: also the live sessions of this process that are not in that store.
<code>x</code>	NULL (the most recently updated stored session), a session id, a file path, or a detached <code>gptr_session</code> .
<code>envir</code>	The home of a rebuilt session.
<code>block, child</code>	A document block id (and a team member name): the session replay bound to that block in this process, or <code>gptr_error_replay_unbound</code> ; never a fallback to <code>envir</code> .

Value

gpnr_sessions() returns a gpnr_sessions data frame: id, file, created, updated, turns, model, status, title (the first prompt, 60 characters), live. gpnr_resume() returns a gpnr_session: the live object when one exists in this process, otherwise one rebuilt from its session file. gpnr_last() returns the most recently active session of this process, or NULL when no session was created in this process.

Examples

```
session = peter("hi", model = gpnr_fake_provider(list("hello")))
identical(gpnr_last(), session)
gpnr_sessions()
identical(gpnr_resume(session$id), session)
```

gpnr_skills	<i>Discovered skills and agents</i>
-------------	-------------------------------------

Description

gpnr_skills() lists the Agent Skills gpnr can see: the project's .gpnr/skills, .agents/skills and .claude/skills, the user's skill directories, the skills of gpnr and of attached packages, and those of enabled plugins. Project skills are listed even when the project is not trusted (their source reads project (untrusted)), but only trusted skills enter the catalog the model sees. gpnr_agents() lists agent definition files the same way. Both only read files.

Usage

```
gpnr_skills(scope = c("all", "project", "user", "packages"))

gpnr_agents(scope = c("all", "project", "user", "packages"))
```

Arguments

scope One of "all", "project", "user" or "packages".

Details

A skill is a directory containing SKILL.md with a YAML description and optional name. Its body is read on demand, or preloaded with peter(skills = "name"). disable-model-invocation: true hides it from automatic catalog selection, while explicit preloading remains available. allowed-tools is metadata, not a permission rule.

Value

gpnr_skills(): a gpnr_skills data frame with columns name, description, source, path, tokens (catalog cost) and visible. gpnr_agents(): a gpnr_agents data frame with columns name, description, model, backend, source and path.

See Also

[gptr_agent](#), [gptr_plugins](#), [gptr_trust](#); `vignette("skills-and-plugins", package = "gptr")` for skills, templates and agent files.

Examples

```
gptr_skills("packages")
gptr_agents()
```

`gptr_source`

Source a history document, regenerating stale blocks without running the old code

Description

Evaluates file top-level expression by expression in `envir`, like `source()` with `keep.source = TRUE`. A `peter()` call whose block is fresh replays without calling a model and the block's code then runs as ordinary R. A call whose block is stale (its prompt or the values interpolated into it changed), or every call under `replay = "live"`, asks the model again and rewrites its block in place, and the old block is skipped, which `base source()` cannot do.

Usage

```
gptr_source(
  file,
  replay = getOption("gptr.replay", "auto"),
  envir = parent.frame(),
  echo = FALSE
)
```

Arguments

<code>file</code>	Path of an .R document.
<code>replay</code>	Replay mode for the calls in the file: "auto", "replay", "live" or "record". A call's own <code>replay =</code> argument wins. Left missing, each call resolves its mode as <code>peter()</code> does: the <code>gptr.replay</code> option, then the <code>GPTR_REPLAY</code> environment variable, then the <code>replay</code> setting, then "auto".
<code>envir</code>	Environment in which the expressions are evaluated.
<code>echo</code>	TRUE prints each expression before it is evaluated.

Details

Replay executes the recorded R code, including its ordinary side effects. It does not freeze package versions, supply external inputs or validate the analysis. This function accepts .R scripts; render .Rmd and .qmd with their report tools, and execute .ipynb through its R kernel. Use [gptr_blocks\(\)](#) to inspect any supported format.

Value

Invisibly, the gp_{tr}_blocks listing of the file after the run with an extra column action: replayed, regenerated, ran, skipped, or NA for blocks no call touched. A stale block whose call ran but could not be rewritten (for example without write consent) is ran and keeps its status.

Examples

```
f = tempfile(fileext = ".R")
writeLines(c("x = 1", "y = x + 1"), f)
gptr_source(f, replay = "replay", envir = new.env())
```

gp_{tr}_spec*Build a spec of any registered kind***Description**

The general constructor behind the eleven spec constructors: it builds a spec of kind from its fields and validates it with the kind's validator. Use it for kinds without a constructor (env_alias, setting, service, preset, ...) and for kinds defined by plugins. Unknown fields are kept (forward compatibility); a wrong type of a known field is an error naming the field.

Usage

```
gptr_spec(kind, name, ...)
```

Arguments

kind	The kind name, one of the kind.<name> features of <code>gp_{tr}_api()</code> .
name	The record name within the kind.
...	The kind's fields, named.

Value

A spec: a list of class `c("gptr_<kind>", "gptr_spec")`.

Examples

```
gptr_spec("env_alias", "SLACK_BOT_TOKEN", aliases = "slack-token")
gptr_spec("setting", "panel.size", default = 3L, description = "Reviewers per panel")
```

gptr_steer

Steer a session

Description

The one enqueue function behind the pipe into a running session, the pause menu and `ctx$send()`. A steer reaches the model after the current tool results, as "The user sent this message while you were working: ..."; a follow-up when the agent would otherwise stop. On an idle session the item is taken when the next run starts.

Usage

```
gptr_steer(s, text, as = c("steer", "follow_up"))
```

Arguments

<code>s</code>	A session.
<code>text</code>	The message (secrets are redacted before it is queued).
<code>as</code>	"steer" or "follow_up".

Value

`s`, invisibly, at once.

Examples

```
session = peter("Summarize mtcars", model = gptr_fake_provider(list("ok")),
  .run = FALSE)
gptr_steer(session, "Use only the mpg column", as = "follow_up")
```

gptr_step

Advance a session

Description

Starts the queued input of an idle session (built with `.run = FALSE`, or given a follow-up with [gptr_steer\(\)](#)) and pumps it until turns model turns have ended or the run settles. A running session is advanced the same way.

Usage

```
gptr_step(s, turns = 1L)
```

Arguments

s	A session.
turns	The number of turns to advance (Inf for all).

Details

.run = FALSE builds a session without making its model request; `gptr_step()` or `gptr_wait()` starts it. Supply an explicit workspace with `envir` = when results must remain available outside the function that creates the session.

Value

s, invisibly. A run that settles in status error, blocked, budget or max_turns signals the condition documented in `peter()`.

Examples

```
session = peter("Plan the analysis", model = gptr_fake_provider(list("Plan: ...")),
  .run = FALSE)
gptr_step(session)
session$turns
```

gptr_tool

Define a tool

Description

A tool is one capability the model can use: declared directly in the request's tool array (exposure = "direct"), callable from R code as `peter$<namespace>$<name>()` ("r", one signature line in the prompt), found through `peter$search()` ("deferred") or callable only by gptr code ("hidden"). Give `execute` (function(input, ctx), the direct-tool form), `fun` (an R function whose formals match the schema properties, the member form), or both. A direct tool with only `fun` gets a generated `execute` that prints the value within `output_tokens`; an `r` member with only `execute` gets a generated `fun`.

Usage

```
gptr_tool(
  name,
  description,
  parameters = NULL,
  execute = NULL,
  fun = NULL,
  exposure = c("direct", "r", "deferred", "hidden"),
  namespace = NULL,
  execution = c("sequential", "concurrent"),
  risk = NULL,
```

```

    snippet = NULL,
    guidelines = NULL,
    signature = NULL,
    output_tokens = NULL,
    record = TRUE,
    available = NULL,
    annotations = list()
  )

```

Arguments

name	Tool name, <code>^[a-zA-Z0-9_-]{1,64}\$</code> .
description	Model-facing description; direct tools stay under 400 estimated tokens.
parameters	A JSON Schema list with type = "object", a function(ctx) evaluated once when a session freezes its prompt, or NULL to derive the schema from fun's formals.
execute	function(input, ctx) returning a gptr_tool_result() , text, a list or NULL.
fun	The R-callable form of the tool.
exposure	One of "direct", "r", "deferred", "hidden".
namespace	Namespace of an r member (plugins must set it to their package name).
execution	"sequential" (tools that evaluate R or write files) or "concurrent".
risk	function(input, ctx) returning a risk level, or NULL.
snippet	One line shown in the prompt's tool list (direct tools).
guidelines	Bullet lines added to the prompt's rules (direct tools).
signature	Catalog line for r members; NULL derives it from the schema.
output_tokens	Budget for printed results; NULL uses the gptr defaults.
record	Keep calls of this member in recorded code.
available	function(ctx) deciding at freeze whether a direct tool is offered.
annotations	Named list: read_only, destructive, idempotent, open_world, requires_user (MCP readOnlyHint-style names are mapped).

Value

A spec of class `c("gptr_tool", "gptr_spec")`.

See Also

[gptr_register](#), [gptr_check](#); `vignette("extending-gptr", package = "gptr")` for complete tool and policy examples.

Examples

```

gptr_tool("nrow_of", "Number of rows of a data frame in the session",
  fun = function(name) nrow(get(name, envir = globalenv())),
  exposure = "r", namespace = "demo")

```

gptr_tool_result	<i>Build a tool result</i>
------------------	----------------------------

Description

What a tool's `execute()` returns: text and images for the model, details kept in the transcript but never sent to a model, and value, the R object handed to R callers of the member (kept in memory only, never persisted).

Usage

```
gptr_tool_result(  
  text = NULL,  
  images = NULL,  
  details = NULL,  
  is_error = FALSE,  
  value = NULL  
)
```

Arguments

text	Character vector, joined with newlines into one text block, or NULL.
images	List of image blocks, PNG file paths or raw PNG vectors, or NULL.
details	Named list of details, or NULL.
is_error	TRUE when the result reports a failure.
value	Any R value returned to R callers.

Value

A `gptr_tool_result` list with content, details, is_error, value, spill, out_id, truncated and terminate.

Examples

```
gptr_tool_result("3 rows", details = list(n = 3L), value = 3L)
```

gptr_trust	<i>Record or read whether a project is trusted</i>
------------	--

Description

Trust decides whether gptr applies or runs what a project directory contains: project settings beyond tightening, .gptr/extensions/ and project plugins, project MCP servers, SYSTEM.md and APPEND_SYSTEM.md, project .env discovery, provider base-URL overrides, the tool and model fields of project agent files, and the authority of project instructions. The decision is kept in tools::R_user_dir("gptr", "config")/trust.json with a fingerprint of the trust-gated files; when they change, the project counts as untrusted again until you confirm. Called from model code during a run, recording a decision is refused.

Usage

```
gptr_trust(path = ".", trust = NULL)
```

Arguments

- path A directory inside the project; its project root is used.
- trust NULL to read the decision, TRUE or FALSE to record one.

Value

With trust = NULL, the recorded decision: TRUE, FALSE or NA (undecided). Otherwise the previous decision, invisibly.

Examples

```
d = tempfile("proj")
dir.create(d)
gptr_trust(d)
unlink(d, recursive = TRUE)
```

gptr_usage	<i>Token usage and cost</i>
------------	-----------------------------

Description

Aggregates the usage rows of sessions (children included, each request counted once) and, for x = NULL, of every live session of this process plus the process System 1 log. Reads only.

Usage

```
gpnr_usage(
  x = NULL,
  by = c("session", "agent", "model", "route"),
  detail = FALSE
)
```

Arguments

<code>x</code>	A <code>gpnr_session</code> , a list of sessions, or <code>NULL</code> (every live session of this process and the System 1 log).
<code>by</code>	Grouping of the summary: "session", "agent", "model" or "route".
<code>detail</code>	<code>FALSE</code> : a <code>gpnr_usage</code> data frame (group, requests, input, output, cache_read, cache_write, cost) with attribute totals; <code>TRUE</code> : the <code>gpnr_ledger</code> per request and context component (request_id, component, tokens, cached) of the sessions' own requests, session by session in request order (a child's requests are in the child's ledger).

Details

Unknown usage stays unknown: a token count or cost that a provider did not report is NA, never zero, so a group or total that includes it is NA and the footer prints it as unknown. A known zero, such as the metered charge of a local model, stays zero. Rows without a session, agent, model or route (process-level System 1 calls) form the NA group.

The detailed component ledger contains estimates; its sum can differ from provider-reported usage. A run's token budget checks estimated next-input tokens and recorded usage before requests; cost limits check recorded cost. The next output or an unknown final charge can exceed a remaining allowance, so these stopping policies are not billing reservations. Teams and fan-outs count child requests against their shared root budget.

Value

A `gpnr_usage` or `gpnr_ledger` data frame.

Examples

```
gpnr_usage()
session = peter("hi", model = gpnr_fake_provider(list("hello")))
gpnr_usage(session)
```

gptr_wait	<i>Wait for sessions to settle</i>
-----------	------------------------------------

Description

Starts idle sessions that have queued input, then pumps until no session is running or waiting, or timeout seconds have passed. Every session's egress and replay checks pass before any is started, so a refusal starts none. On timeout the sessions keep their running status and no condition is raised.

Usage

```
gptr_wait(x, timeout = Inf)
```

Arguments

x	A session or a list of sessions (a team or fan-out session counts as one).
timeout	Seconds to wait.

Details

timeout limits reactor polling; it does not interrupt R code. Request preparation and synchronous callbacks finish their current step before the deadline is checked again, so a call can return after the specified time.

A timeout is not cancellation. Inspect `$status` and use `gptr_cancel()` if you want to abort active work. In Rscript and rendered reports, a blocking call such as this is how experimental background sessions progress when there is no idle console.

Value

x, invisibly. For a single session, a terminal status signals its condition.

Examples

```
fake = gptr_fake_provider(list("a"))
runs = list(a = peter("one", model = fake, .run = FALSE),
            b = peter("two", model = fake, .run = FALSE))
gptr_wait(runs, timeout = 10)
vapply(runs, function(x) x$status, "")
```

peter *Run an agent in this R session*

Description

`peter()` is the single entry point. Give it a quoted prompt and, optionally, the objects the agent should work on; it returns the agent session, which you can print, query (`$text`, `$value`, `$usage`) and continue with the pipe. Models, modes, skills, plugins, extensions and tools may be written as bare names.

Usage

```
peter(..., model = NULL, mode = NULL, skills = NULL, plugins = NULL,
      extensions = NULL, tools = NULL, agents = NULL, parallel = NULL,
      choices = NULL, levels = NULL, threshold = 0.5,
      min_confidence = NULL, uncertain = NULL,
      prompt = NULL, envir = parent.frame(), background = FALSE,
      budget = NULL, replay = NULL, .opts = list(), .run = TRUE,
      .stdin = FALSE)
```

Arguments

<code>...</code>	A session to continue, the prompt, and context objects.
<code>model</code>	A model name (sonnet, "anthropic/claude-sonnet-5-5"), a provider or router spec such as <code>gptr_fake_provider()</code> , or NULL for the configured default.
<code>mode</code>	One of plan, manual, edits, auto; NULL for the configured default.
<code>skills, plugins, extensions</code>	Names (bare or quoted) of skills to preload, plugins and extensions to enable for this session; extensions also takes function(<code>gptr</code>) factories and file paths.
<code>tools</code>	Tool names, "+name"/"-name" modifiers, a preset name, or <code>gptr_tool()</code> specs.
<code>agents</code>	A named list of agent definitions for a team (<code>agent()</code> means <code>gptr_agent()</code>).
<code>parallel</code>	Fan one list-like context object out over this many concurrent sub-agents.
<code>choices, levels, threshold, min_confidence, uncertain</code>	System 1 answer shape and abstention.
<code>prompt</code>	An explicit prompt; wins over positional selection.
<code>envir</code>	Where the agent evaluates R code and creates objects.
<code>background</code>	Experimental: return the running session at once (needs later).
<code>budget</code>	<code>list(tokens =, cost =, turns =)</code> limits for this call.
<code>replay</code>	Document replay mode: "auto", "replay", "live" or "record".
<code>.opts</code>	Rare switches such as thinking, max_turns, context, returns, images, preset, and entries named by a plugin namespace.
<code>.run</code>	FALSE builds the session with the prompt queued and returns it (see <code>gptr_step()</code>).
<code>.stdin</code>	Drive the console from piped standard input.

Details

Conversational agents compute in memory: their R tools use the objects already loaded in `envir`, and later turns can reuse fitted models and intermediate results without saving and reloading the dataset. Model context contains bounded descriptions and requested results; R computes on the full local object. Ordinary R allocations, file-backed inputs, checkpoints and worker transfers still have their usual costs. See `vignette("execution-model", package = "gptr")` for these boundaries.

The dots take, in order: at most one leading session to continue, the prompt (the first unnamed string literal, else the first unnamed length-1 character value), and context objects (unnamed ones are labeled by their expression, named ones by name). Conversational context bindings refer to objects where they live; descriptions are budgeted separately from in-memory R computation. Every other argument is matched by its exact name only.

A literal prompt gets `{name}` interpolation from `envir` (atomic vectors of 1 to 50 values; `{{` and `}}` are literal braces); `.opts = list(interpolate = FALSE)` switches it off.

Terminal statuses become conditions carrying the session as `$session`: error signals `gptr_error_provider`, blocked `gptr_error_permission`, budget `gptr_error_budget_<kind>` and max_turns `gptr_error_max_turns`. `peter()` with no prompt opens the console when someone can answer, and signals `gptr_error_noninteractive` otherwise.

A new interactive console without an explicit or configured model first offers CLI selection or manual API/Ollama instructions. Selecting an available CLI saves its default at user scope; cancellation or manual setup returns without starting a session. Existing sessions, explicit or configured models and `.stdin = TRUE` skip setup. CLI-reported login is not proof of online access or subscription billing. See `vignette("interactive-console", package = "gptr")`.

The name honors Peter Cathcart Wason, whose research with Jonathan Evans distinguished processes underlying reasoning and introspection, and Peter Naur of the Backus-Naur form, in the spirit of recording sessions as readable, replayable documents. A user object named `peter` hides the gateway; call `gptr::peter()` then.

Value

A `gptr_session` for agent work (invisibly when its answer was streamed to the console), or a typed System 1 vector for classifier models.

The interactive console

`peter()` without a prompt opens a console when someone can answer (interactive R or IRkernel); `peter(.stdin = TRUE)` reads its input from standard input, and `session |> peter()` opens it on `session`. With no explicit or configured model, the interactive console first offers Codex CLI, Claude Code CLI or API configuration instructions. Choosing an available CLI saves its default model at user scope; cancelling returns to R. Piped input skips this setup. Each input is one of:

- a prompt, sent as `session |> peter("...")` with `{name}` interpolation; `@file` adds the head of a file (at most 40 lines) and `@object` attaches an object by name;
- `!code`: R code run in the session's environment; the code and its output go with the next prompt (at most 300 estimated tokens). `!!code` omits that note. Both execute your own R immediately, without the model's permission gate or a model request. Workspace changes remain visible to later calls, and enabled transcripts can record the code; `!!` is not a privacy

boundary. A fenced R block works like `!code`, a `"""` block is a multi-line prompt, and a trailing backslash continues a line;

- a slash command such as `/model`, `/mode`, `/cost` or `/exit`; `/help` lists them all.

Ctrl-C while an answer runs opens a pause menu in supported terminal front ends: `[s]teer` (delivered after the current tool results), `[f]ollow-up`, `[c]ontinue`, `[a]bort` and, for a foreground call (including a chat turn) when available, `[b]ackground`; a second Ctrl-C aborts. Backgrounding returns to the chat prompt; use `!!gptr::gptr_wait(gptr::gptr_last())` there to wait for completion. Returning to the prompt does not guarantee progress while the chat waits for input. Under Rscript, background runs advance only inside blocking `gptr` calls. Front ends that cannot resume use an abort fallback. `/exit`, two consecutive interrupts at the prompt or the end of piped input return the session invisibly, so `session = peter()` keeps the conversation. Use Ctrl-C in a terminal; RStudio, R.app, RGui and Positron use Esc.

Options: `gptr.verbose` (0 silent, 1 progress, 2 streamed console, 3 debug; default 0 in knitr and testthat, 1 under Rscript, 2 at the console), `gptr.max_turns_console` (turns per console prompt, default 200) and `gptr.history` (console inputs to R's history, default TRUE). Ordinary progress uses normal output; actual errors use `stderr`. `vignette("interactive-console", package = "gptr")` gives input examples and the complete built-in command table.

Sessions and results

A pipe such as `session |> peter("Explain the result.")` adds work to the same session and kept workspace. Use `gptr_fork()` to branch explicitly. The final answer is `session$text`; `session$value` is the R value selected by `gptr_return()` during a tool call. Agent-created objects remain in `envir`.

See Also

[gptr_security](#), [gptr_egress](#) and [gptr_options](#); `vignette("language-models", package = "gptr")` for connecting models and scripted calls.

Examples

```
fake = gptr_fake_provider(list("The data has 32 rows.", "The data has 11 columns."))
session = peter("How many rows does the data have?", mtcars, model = fake)
session$text
session |> peter("And how many columns?")
identical(gptr_last(), session)
```

print.gptr_session *Print a session*

Description

The footer is `status . model . turns . tokens . cost . id`. A token count or cost that a provider did not report is printed as `unknown`, never as `zero`.

Usage

```
## S3 method for class 'gptr_session'  
print(x, ...)
```

Arguments

x	A gptr_session.
...	Unused.

Value

x, invisibly.

print.gptr_session_summary
<i>Print a session summary</i>

Description

Display the latest recorded messages at the current console width. This changes neither the complete history table nor the session, and makes no model request. Unknown token counts remain unknown. Previews are single lines; the underlying table retains its text.

Usage

```
## S3 method for class 'gptr_session_summary'  
print(x, n = 8L, ...)
```

Arguments

x	A gptr_session_summary.
n	Maximum number of recent messages to display; Inf displays every row.
...	Unused.

Value

x, invisibly.

str.gptr_session	Show a session's structure
------------------	----------------------------

Description

Show a session's structure

Usage

```
## S3 method for class 'gptr_session'  
str(object, ...)
```

Arguments

object	A gptr_session.
...	Unused.

Value

NULL, invisibly.

summary.gptr_session	Summarize a session as its history
----------------------	------------------------------------

Description

Reads a table of recorded turns without a model request. It does not generate a narrative workflow summary or export an executable script. To request prose, continue the session with [peter\(\)](#) and verify the model-generated answer against the recorded work. Both `summary(session)` and `session$history` retain every recorded message. Printing shows the latest eight messages and a snapshot of session metadata. Notebook, R Markdown and Quarto displays use the same compact preview by default. Use `print(x, n = Inf)` to display every row, or `as.data.frame(x)` for an ordinary data frame without the display metadata.

Usage

```
## S3 method for class 'gptr_session'  
summary(object, ...)
```

Arguments

object	A gptr_session.
...	Unused.

Value

A `gptr_session_summary` data frame (turn, role, preview, tools, tokens).

Index

as.character.gptr_session
 (format.gptr_session), 5
as.data.frame.gptr_session_summary, 4

background-sessions (gptr-background), 6

format.gptr_risk, 4
format.gptr_session, 5

gptr-background, 6
gptr_adapter, 7
gptr_agent, 8, 62
gptr_agent(), 71
gptr_agents (gptr_skills), 61
gptr_api, 9
gptr_api(), 63
gptr_artifacts, 10
gptr_backend, 11
gptr_blocks, 12
gptr_blocks(), 24, 62
gptr_cache, 12
gptr_cancel, 6, 7, 13
gptr_cancel(), 70
gptr_check, 14, 42, 66
gptr_checkpoints (gptr_rewind), 53
gptr_command, 15
gptr_config, 15
gptr_config(), 22, 33, 35, 39
gptr_context_block, 17
gptr_describe, 18
gptr_doc, 19
gptr_doc(), 24, 58
gptr_egress, 21, 39, 45, 58, 60, 73
gptr_env, 22
gptr_env(), 38
gptr_export, 23
gptr_fake_provider, 24
gptr_fake_provider(), 22, 71
gptr_fork, 26
gptr_fork(), 53, 73

gptr_hook, 26
gptr_init, 27
gptr_init(), 16, 58, 59
gptr_jobs, 6, 7, 28
gptr_last (gptr_sessions), 60
gptr_last(), 32
gptr_login, 29, 30
gptr_logout (gptr_login), 29
gptr_mcp, 30
gptr_mcp_add, 30, 31
gptr_mcp_remove, 30
gptr_mcp_remove (gptr_mcp_add), 31
gptr_mcp_serve, 30, 32
gptr_mcp_serve(), 60
gptr_models, 33
gptr_on, 34
gptr_options, 16, 22, 35, 60, 73
gptr_parallel, 39
gptr_parallel(), 36
gptr_permissions, 40
gptr_permissions(), 16, 60
gptr_plugins, 41, 62
gptr_policy, 42
gptr_preimage, 43
gptr_prob, 44
gptr_prompt, 45
gptr_prompt_section, 46
gptr_provider, 47
gptr_providers, 48
gptr_providers(), 22, 34
gptr_redact, 49
gptr_register, 50, 66
gptr_registry, 42, 51
gptr_reload, 42, 51
gptr_resume (gptr_sessions), 60
gptr_return, 52
gptr_return(), 73
gptr_rewind, 53
gptr_rewind(), 58

gptra_risk, 55
gptra_risk(), 58, 60
gptra_router, 56
gptra_scrub, 57
gptra_scrub(), 59, 60
gptra_security, 22, 39, 58, 73
gptra_sessions, 60
gptra_skills, 61
gptra_source, 62
gptra_source(), 24
gptra_spec, 63
gptra_spec(), 50
gptra_steer, 7, 64
gptra_steer(), 64
gptra_step, 64
gptra_step(), 65, 71
gptra_tool, 65
gptra_tool(), 71
gptra_tool_result, 67
gptra_tool_result(), 66
gptra_trust, 62, 68
gptra_trust(), 16, 27, 59, 60
gptra_usage, 68
gptra_wait, 6, 7, 70
gptra_wait(), 65

peter, 7, 71
peter(), 16, 34–36, 39, 58, 65, 75
print.gptra_prompt_view(gptra_prompt), 45
print.gptra_risk(format.gptra_risk), 4
print.gptra_session, 73
print.gptra_session_summary, 74

source(), 62
str.gptra_session, 75
summary.gptra_session, 75
Sys.setenv(), 22